



24P3CV

23.8" FHD 3-sided flat IPS display for easy and consistent productivity

The AOC 24P3CV is a 23.8" flat-screen IPS monitor with an attractive three-sided ultrathin bezel design that helps you get the most out of your flexible work style. Enjoy vivid, realistic picture quality thanks to enhanced Full HD (1920 x 1080) resolution, paired with 300-nit brightness and generous 178/178° wide viewing angles. This model features built-in 2W + 2W speakers to let you enjoy the media whenever you need. Monitor 24P3CV is ready to boost your productivity with USB-C supporting Power Delivery up to 65W, data transfer and DP-alt mode. Connectivity of this monitor is enhanced with USB Hub, RJ-45 & DP-out. Keeping sustainability in mind, an array of environmental certifications including EPA, TCO, and EPEAT complete this monitor.

GENERAL	
Model Name	24P3CV
EAN	4038986140751
Channel	B2B
Product line	Pro-line Pro-line
Design family	P3
Launch date (ETA)	2/14/2023

1/4



SCREEN	
Screen size (inch)	23.8
Screen size (cm)	60.5
Flat / Curved	Flat
Display hardness	3H
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	IPS
Backlight type	WLED
Max Refresh rate	75 Hz
Response time GtG	4 ms
Static contrast ratio	1000:1
Dynamic contrast ratio	50M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0.2745
Pixels per Inch	93

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100×100
Tilt	-5/35
Swivel	180°
Pivot	-90°~90°
Height adjust (mm)	150mm



CONNECTIVITY AND MULTIMEDIA	
НДМІ	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.4 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	/
USB Hub speed	USB 3.2
USB downstream ports	4
RJ45	1x 10M/100M/1G
DisplayPort output	1x DP-Out 1.2

MULTIMEDIA	
Speakers	/
Speaker power	2 W x 2
Audio Output	1x Audio out

FEATURES	
Sync technology (VRR)	Adaptive Sync
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	✓
Colour space (sRGB) CIE 1976 %	124.3
Colour space (DCI-P3) CIE 1976 %	93.9

SUSTAINABILITY	
TCO Certified	9
Energy star	Energy star 8
EPEAT	Gold

POWER / ENVIRONMENTAL	
Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3
Energy class	E

3 / 4



PRODUCT DIMENSIONS	
Product dimensions incl. base (WxHxD) mm	540(W)x (384.4-502.9)(H)x 200.1(D)
Product dimensions excl. base (WxHxD) mm	540(W)x 326.3(H)x 50.7(D)
Packaging dimensions (WxHxD) mm	613 (W) x 519 (H) x 162 (D)
Gross weight incl. package (in kg)	8.31
Net weight excl. package (in kg)	5.37
Product without stand (kg)	3.66

WHAT'S IN THE BOX	
HDMI cable	1.8
Displayport cable	1.8
USB-C to C/A cable	1.8
Power Cable	
Power cable C13	1.8

OTHER INFORMATION	
MTBF	70.000 hours (excluded backlight) + 30.000 hours (including backlight)
MTBF (excluding panel)	70.000 hours
MTBF (including panel)	30.000 hours