



X24P1

24", 3-sides frameless IPS display with 16:10 aspect ratio

The 16:10 aspect ratio and 1920x1200 resolution of the 24" sized, 3-sides frameless X24P1 is suited perfectly for productivity tasks (spreadsheets, texts). X24P1 comes with a fully adjustable stand with 150 mm height range, capable of pivot mode. It is also fully equipped with VGA, DVI, HDMI and DisplayPort inputs, a built-in USB 3.0 hub and speakers.

GENERAL	
Model Name	X24P1
EAN	4038986146241
Channel	В2В
Product line	Pro-line
Design family	P1
Launch date (ETA)	6/29/2018

Screen size (inch) 24 Screen size (cm) 60.96 Flat / Curved Flat Display hardness 3H Panel resolution 1920x1200 Resolution name WUXGA Aspect ratio 16:10 Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2 Pixel Pitch (mm) 0.27	SCREEN	
Flat / Curved Display hardness 3H Panel resolution 1920x1200 Resolution name WUXGA Aspect ratio 16:10 Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio Dynamic contrast ratio 16:7 Million Display colours 16:7 Million Brightness in nits 300 cd/m2	Screen size (inch)	24
Display hardness 3H Panel resolution 1920x1200 Resolution name WUXGA Aspect ratio 16:10 Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Screen size (cm)	60.96
Panel resolution 1920x1200 Resolution name WUXGA Aspect ratio 16:10 Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Flat / Curved	Flat
Resolution name WUXGA Aspect ratio 16:10 Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Brightness in nits WUXGA WUXGA 16:10 1000:1 Panel type WLED WLED WLED WLED WLED 178/178 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1 1000:1	Display hardness	3H
Aspect ratio 16:10 Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Panel resolution	1920x1200
Panel type IPS Backlight type WLED Max Refresh rate 60 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Resolution name	WUXGA
Backlight typeWLEDMax Refresh rate60 HzResponse time GtG4 msStatic contrast ratio1000:1Dynamic contrast ratio50M:1Viewing angle (CR10)178/178Display colours16.7 MillionBrightness in nits300 cd/m2	Aspect ratio	16:10
Max Refresh rate60 HzResponse time GtG4 msStatic contrast ratio1000:1Dynamic contrast ratio50M:1Viewing angle (CR10)178/178Display colours16.7 MillionBrightness in nits300 cd/m2	Panel type	IPS
Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Backlight type	WLED
Static contrast ratio 1000:1 Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Max Refresh rate	60 Hz
Dynamic contrast ratio 50M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 300 cd/m2	Response time GtG	4 ms
Viewing angle (CR10)178/178Display colours16.7 MillionBrightness in nits300 cd/m2	Static contrast ratio	1000:1
Display colours 16.7 Million Brightness in nits 300 cd/m2	Dynamic contrast ratio	50M:1
Brightness in nits 300 cd/m2	Viewing angle (CR10)	178/178
	Display colours	16.7 Million
Pixel Pitch (mm) 0.27	Brightness in nits	300 cd/m2
	Pixel Pitch (mm)	0.27

1/3



EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100×100
Tilt	-5/35
Swivel	-175/175
Pivot	Yes
Height adjust (mm)	150mm

CONNECTIVITY AND MULTIMEDIA	
НДМІ	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.2 x 1
USB Hub	/
USB Hub speed	USB 3.1 (Gen 1) (4 USB downstream ports)
USB downstream ports	4
USB fast charge port	/
D-SUB (VGA)	1x
DVI	1x DVI-D

MULTIMEDIA	
Speakers	/
Speaker power	2 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES	
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	✓ ·
Colour space (Adobe RGB) CIE 1931 %	77



SUSTAINABILITY	
TCO Certified	7
Energy star	Energy star 8
EPEAT	Silver

POWER / ENVIRONMENTAL	
Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.32
Power consumption off in watts	0.23
Energy class	E

PRODUCT DIMENSIONS	
Product dimensions incl. base (WxHxD) mm	533.5(H) × 535.23(W) × 202.96(D)
Packaging dimensions (WxHxD) mm	422(H) × 752(W) × 168(D)
Gross weight incl. package (in kg)	7.5
Net weight excl. package (in kg)	5.5

WHAT'S IN THE BOX	
HDMI cable	1.8
Displayport cable	1.8
Audio cable	1.8
Power cable C13	1.8

OTHER INFORMATION	
MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

3/3