



E2460SD2

Vivid imagery, versatile productivity

This model targets business and home office users alike. Hidden behind its classically designed case is the latest LED technology. It boasts a high typical contrast, an ultra-fast 1ms response time and wide viewing angles for excellent imaging performance. The environmentally friendly display comes in an elegant, textured black finish.

| GENERAL | |
|-------------------|----------------|
| Model Name | E2460SD2 |
| EAN | 4038986145213 |
| Channel | B2B |
| Product line | Essential-line |
| Design family | 60 ID |
| Launch date (ETA) | 3/1/2015 |

| SCREEN | |
|------------------------|--------------|
| Screen size (inch) | 24 |
| Flat / Curved | Flat |
| Display hardness | ЗН |
| Panel resolution | 1920x1080 |
| Resolution name | FHD |
| Aspect ratio | 16:9 |
| Panel type | TN |
| Backlight type | WLED |
| Max Refresh rate | 60 Hz |
| Response time GtG | 1 ms |
| Static contrast ratio | 1000:1 |
| Dynamic contrast ratio | 20M:1 |
| Viewing angle (CR10) | 170/160 |
| Display colours | 16.7 Million |
| Brightness in nits | 250 cd/m2 |
| Pixel Pitch (mm) | 276 |

1/3



| ERGONOMICS | |
|----------------|---------|
| Vesa wallmount | 100x100 |
| Pivot | No |

| CONNECTIVITY AND MULTIMEDIA | |
|-----------------------------|----------|
| USB Hub | - |
| USB fast charge port | - |
| D-SUB (VGA) | 1x |
| DVI | 1x DVI-D |

| MULTIMEDIA | |
|---------------------|---|
| Built-in Microphone | - |

| FEATURES | |
|-----------------|----|
| Flicker-Free | No |
| Kensington Lock | - |

| SUSTAINABILITY | |
|----------------|---|
| TCO Certified | 6 |

| POWER / ENVIRONMENTAL | |
|------------------------------------|--------------------|
| Power supply | Internal |
| Power source | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0.29 |
| Power consumption off in watts | 0.13 |

| PRODUCT DIMENSIONS | |
|---|---------------------------------|
| Product dimensions incl. base (WxHxD) mm | 403.05(H) x 565.4(W) x 219.3(D) |
| Packaging dimensions (WxHxD) mm | 131(H) x 621(W) x 476(D) |
| Gross weight incl. package (in kg) | 6.1 |
| Net weight excl. package (in kg) | 4.64 |

2/3



| WHAT'S IN THE BOX | |
|-------------------|-----|
| D-SUB (VGA) cable | 1.2 |
| DVI cable | 1.5 |
| Power cable C7 | 1.2 |

| OTHER INFORMATION | |
|------------------------|-----------------------------------|
| MTBF | 50.000 hours (excluded backlight) |
| MTBF (excluding panel) | 50.000 hours |

| REGULATORY COMPLIANCE | |
|-----------------------|---|
| ISO 9241-307 | / |