



## 27B3CF2

Compact brilliance with USB-C connectivity and Height-Adjustable Stands for enhanced productivity

Introducing the newest addition to the B3 line— a brilliant 27-inch display featuring an IPS panel for breathtaking visuals and true-to-life colors. If you're looking for something larger than 23.8 inches, the 27B3CF2 is the ideal choice. With USB-C implementation, video signal, power delivery and data transfer are possible at the same time. The monitor boasts the same features as the 24B3CF2, which means it provides height-adjustable stands, seamlessly integrating ergonomic features into your workspace. With the ability to customize the height according to your preferences, you can achieve the perfect viewing angle, reducing strain on your neck and eyes during extended work or studying sessions. Whether you're working or studying, enjoy a more comfortable and enjoyable viewing experience with the expansive screen size of the 27B3CF2.

| GENERAL           |               |
|-------------------|---------------|
| Model Name        | 27B3CF2       |
| EAN               | 4038986181457 |
| Channel           | B2C           |
| Product line      | Basic-line    |
| Design family     | B3            |
| Launch date (ETA) | 1/1/2024      |

1/4



| SCREEN                 |                |
|------------------------|----------------|
| Screen size (inch)     | 27             |
| Screen size (cm)       | 68.6           |
| Flat / Curved          | Flat           |
| Display hardness       | ЗН             |
| Panel treatment        | Antiglare (AG) |
| Panel resolution       | 1920x1080      |
| Resolution name        | FHD            |
| Aspect ratio           | 16:9           |
| Panel type             | IPS            |
| Backlight type         | WLED           |
| Max Refresh rate       | 100 Hz         |
| Response time GtG      | 4 ms           |
| Response time MPRT     | 1 ms           |
| Static contrast ratio  | 1300:1         |
| Dynamic contrast ratio | 20M:1          |
| Viewing angle (CR10)   | 178/178        |
| Display colours        | 16.7M (8bits)  |
| Brightness in nits     | 250 cd/m2      |
| Pixel Pitch (mm)       | 0.3114         |
| Pixels per Inch        | 82             |

| EXTERIOR                     |              |
|------------------------------|--------------|
| Bezel type (front)           | Ultra Narrow |
| Bezel Colour (front)         | Black        |
| Bezel finishing (front)      | Texture      |
| Cabinet colour (backside)    | Black        |
| Cabinet finishing (backside) | Texture      |

| ERGONOMICS         |          |
|--------------------|----------|
| Vesa wallmount     | 100×100  |
| Tilt               | -5 / +25 |
| Swivel             | No       |
| Pivot              | No       |
| Height adjust (mm) | 110mm    |



| CONNECTIVITY AND MULTIMEDIA |  |
|-----------------------------|--|
| НДМІ                        | HDMI 1.4 x 1   |
| Digital HDCP (HDMI version) | HDCP 1.4   |
| USB-C connectivity          | USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W) |
| USB Hub                     | ✓  |
| USB Hub speed               | USB 3.2 (Gen 1)  |
| USB downstream ports        | 2  |
| USB fast charge port        | ✓  |
| RJ45                        | No   |
| D-SUB (VGA)                 | 0x   |
| DVI                         | 0x   |

| MULTIMEDIA          |                       |
|---------------------|-----------------------|
| Speakers            | ✓ ·                   |
| Speaker power       | 2 W x 2               |
| Built-in Microphone | -                     |
| Audio Output        | Headphone out (3.5mm) |
| MonitorWebcam       | No                    |

| FEATURES                               |                |
|--|----------------|
| Sync technology (VRR)                  | Adaptive Sync  |
| Blue Light Technology                  | Low Blue Light |
| Flicker-Free                           | Flicker Free   |
| KVM                                    | No             |
| Kensington Lock                        | ✓              |
| Colour space (sRGB) CIE 1976 %         | 101.4          |
| Colour space (DCI-P3) CIE 1931 %       | 75             |
| Colour space (DCI-P3) CIE 1976 %       | 80.7           |
| Colour space (Adobe RGB) CIE 1931<br>% | 75.4           |
| Colour space (Adobe RGB) CIE 1976<br>% | 86.9           |

| SUSTAINABILITY |               |
|----------------|---------------|
| TCO Certified  | No            |
| Energy star    | Energy star 8 |



| POWER / ENVIRONMENTAL              |                    |
|------------------------------------|--------------------|
| Power supply                       | Internal           |
| Power source                       | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0.5                |
| Power consumption off in watts     | 0.3                |
| Energy class                       | E                  |

| PRODUCT DIMENSIONS                          |                               |
|---|-------------------------------|
| Product dimensions incl. base<br>(WxHxD) mm | 616.6 x (398.6-508.6) x 229.8 |
| Product dimensions excl. base<br>(WxHxD) mm | 616.6 x 45.3 x 356.7          |
| Packaging dimensions (WxHxD) mm             | 820 x 162 x 481               |
| Packaging dimensions (WxHxD) mm (CN)        | 820 x 162 x 481               |
| Gross weight incl. package (in kg)          | 8.71                          |
| Net weight excl. package (in kg)            | 5.56                          |
| Gross weight incl. package (in kg) (CN)     | 8.71                          |
| Product without stand (kg)                  | 4.03                          |

| WHAT'S IN THE BOX                             |     |
|---|-----|
| HDMI cable                                    | 1.5 |
| USB-C to C cable                              | 1.8 |
| RS232   | -   |
| Power Cable                                   | /   |
| Color and brightness uniformity report in box | -   |