



## CU34V5C/BK

**34" VA WQHD panel for maximum productivity, with MultiView, USB-C and PD65W**

The AOC CU34V5C is equipped with a 34" VA curved panel with Ultrawide QHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and height adjust as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.

GENERAL	
Model Name	CU34V5C/BK
EAN	4038986110198
Channel	B2C
Product line	Value-line
Design family	V5
Launch date (ETA)	7/18/2022

SCREEN	
Screen size (inch)	34
Screen size (cm)	86.4
Flat / Curved	Curved
Curvature Radius	1500R
Display hardness	6H
Panel treatment	Antiglare (AG)
Panel resolution	3440x1440
Resolution name	WQHD
Aspect ratio	21:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	100 Hz
Response time GtG	4 ms
Response time MPRT	1 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m <sup>2</sup>
Pixel Pitch (mm)	0.23175
Pixels per Inch	109.7

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Matt
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Matt

ERGONOMICS	
Vesa wallmount	100x100
Tilt	3° ±2° ~ 21° ±2°
Swivel	28° ±2° ~ 28° ±2°
Pivot	No
Height adjust (mm)	130mm

**CONNECTIVITY AND MULTIMEDIA**

HDMI	HDMI 2.0 x 1
Digital HDCP (HDMI version)	HDCP 2.2
DisplayPort	DisplayPort 1.2 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	✓
USB Hub speed	USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit
USB downstream ports	4
USB fast charge port	✓
RJ45	No
D-SUB (VGA)	0x
DVI	0x

**MULTIMEDIA**

Speakers	✓
Speaker power	5 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)
MonitorWebcam	No

**FEATURES**

Sync technology (VRR)	Freesync
Blue Light Technology	Low Blue Light
Multiview (PbP, PiP)	PbP, PiP
Flicker-Free	Flicker Free
KVM	No
Kensington Lock	✓
Colour space (sRGB) CIE 1976 %	116
Colour space (DCI-P3) CIE 1931 %	90
Colour space (DCI-P3) CIE 1976 %	93
Colour space (Adobe RGB) CIE 1931 %	90
Colour space (Adobe RGB) CIE 1976 %	100

**POWER / ENVIRONMENTAL**

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3
Energy class	G

**PRODUCT DIMENSIONS**

Product dimensions incl. base (WxHxD) mm	808.1x(397.3~527.3)x250mm
Product dimensions excl. base (WxHxD) mm	808.1x365.3x99.9mm
Packaging dimensions (WxHxD) mm	1071x189x500mm
Gross weight incl. package (in kg)	11.75
Net weight excl. package (in kg)	9.34

**WHAT'S IN THE BOX**

HDMI cable	1.5
USB-C to C cable	1.8
Power Cable	✓

**OTHER INFORMATION**

MTBF	50.000 hours (excluded backlight)
MTBF (including panel)	50.000 hours