



24B2XH/EU

Thin and sleek 23.8" IPS monitor with lively colours, wide angle visibility and eye-friendly technology

The 24B2XH from the B2 Series employs a 23.8" Full HD IPS panel offering wide viewing angles, accurate and lively colours plus flexible connectivity. It features a slim profile and a 3-sides borderless panel for seamless multi monitor setups. Say goodbye to eyestrain thanks to AOC's LowBlue and FlickerFree technologies.

GENERAL	
Model Name	24B2XH/EU
Channel	B2C
Product line	Basic-line
Design family	B2
Launch date (ETA)	11/1/2020

Screen size (inch) 23.8 Screen size (cm) 60.452 Flat / Curved Flat Display hardness 3H Panel treatment Antiglare (AG) Panel resolution 1920x1080 Resolution name FHD Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	SCREEN	
Flat / Curved Display hardness 3H Panel treatment Antiglare (AG) Panel resolution 1920x1080 Resolution name FHD Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) Pixel Pitch (mm)	Screen size (inch)	23.8
Display hardness 3H Panel treatment Antiglare (AG) Panel resolution 1920x1080 Resolution name FHD Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Screen size (cm)	60.452
Panel treatment Antiglare (AG) Panel resolution 1920x1080 Resolution name FHD Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Flat / Curved	Flat
Panel resolution 1920x1080 Resolution name FHD Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Display hardness	3H
Resolution name Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm)	Panel treatment	Antiglare (AG)
Aspect ratio 16:9 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Panel resolution	1920x1080
Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Resolution name	FHD
Backlight type WLED Max Refresh rate 75 Hz Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Aspect ratio	16:9
Max Refresh rate75 HzResponse time GtG4 msStatic contrast ratio1000:1Dynamic contrast ratio20M:1Viewing angle (CR10)178/178Display colours16.7 MillionBrightness in nits250 cd/m2Pixel Pitch (mm)0.2745	Panel type	IPS
Response time GtG 4 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Backlight type	WLED
Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Max Refresh rate	75 Hz
Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Response time GtG	4 ms
Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Static contrast ratio	1000:1
Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Dynamic contrast ratio	20M:1
Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.2745	Viewing angle (CR10)	178/178
Pixel Pitch (mm) 0.2745	Display colours	16.7 Million
	Brightness in nits	250 cd/m2
	Pixel Pitch (mm)	0.2745
Pixels per Inch 93	Pixels per Inch	93

1/3



EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100x100
Tilt	-5/20
Pivot	No

CONNECTIVITY AND MULTIMEDIA	
HDMI	HDMI 1.4 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x

MULTIMEDIA	
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES	
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	✓
Colour space (Adobe RGB) CIE 1931 %	78

SUSTAINABILITY	
Energy star	Energy star 8

2/3



POWER / ENVIRONMENTAL	
Power supply	External
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.3
Power consumption off in watts	0.3
Energy class	E

PRODUCT DIMENSIONS (METRIC)	
Product dimensions incl. base (WxHxD) mm	418.35(H) x 539.47(W) x 170.94(D)
Product dimensions excl. base (WxHxD) mm	320.94(H) x 539.47(W) x 37.6(D)
Packaging dimensions (WxHxD) mm	467(H) x 592(W) x 106(D)
Gross weight incl. package (in kg)	4.5
Product with stand (kg)	2.7

WHAT'S IN THE BOX	
HDMI cable	1.8
Power cable C13	1.8

OTHER INFORMATION	
MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE	
ISO 9241-307	✓