



U34V5C/BK

34" VA WQHD display for the most complex multitasking, with USB-C and PD65W

The AOC U34V5C is equipped with a 34" VA panel with WQHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and adjust the height as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.

GENERAL

Model Name	U34V5C/BK
Channel	B2C
Product line	Value-line
Design family	V5
Launch date (ETA)	10/13/2022

SCREEN

Screen size (inch)	34
Screen size (cm)	86.4
Flat / Curved	Flat
Display hardness	6H
Panel treatment	Antiglare (AG)
Panel resolution	3440x1440
Resolution name	WQHD
Aspect ratio	21:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	100 Hz
Response time GtG	4 ms
Static contrast ratio	4000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0.23175
Pixels per Inch	109

EXTERIOR

Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Matt
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Matt

ERGONOMICS

Vesa wallmount	100x100
Tilt	-3.5° ±1.5° ~ 21.5° ±1.5°
Swivel	-8° ±2°
Pivot	No
Height adjust (mm)	130mm

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 2.0 x 1
Digital HDCP (HDMI version)	HDCP 2.0
DisplayPort	DisplayPort 1.2 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	✓
USB Hub speed	USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit
USB downstream ports	4
USB fast charge port	✓
RJ45	No
D-SUB (VGA)	0x
DVI	0x

MULTIMEDIA

Speakers	✓
Speaker power	5 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)
Monitor Webcam	No

FEATURES

Sync technology (VRR)	Adaptive Sync
Blue Light Technology	Low Blue Light
Multiview (PbP, PiP)	PbP, PiP
Flicker-Free	Flicker Free
KVM	No
Kensington Lock	✓
Colour space (sRGB) CIE 1976 %	115
Colour space (DCI-P3) CIE 1931 %	89
Colour space (DCI-P3) CIE 1976 %	91
Colour space (Adobe RGB) CIE 1931 %	90
Colour space (Adobe RGB) CIE 1976 %	98

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3
Energy class	G

PRODUCT DIMENSIONS (METRIC)

Product dimensions incl. base (WxHxD) mm	817.45 x (404.55~534.55) x 250
Product dimensions excl. base (WxHxD) mm	817.45 x 370.69 x 55.34
Packaging dimensions (WxHxD) mm	1070 x 481 x 162
Gross weight incl. package (in kg)	11.65
Product with stand (kg)	9.14
Product without stand (kg)	6.56

WHAT'S IN THE BOX

HDMI cable	1.5
USB-C to C cable	1.8

OTHER INFORMATION

MTBF	50.000 hours (excluded backlight)
MTBF (including panel)	50.000 hours