



24P3CV

23.8" FHD 3-sided flat IPS display for easy and consistent productivity

The AOC 24P3CV is a 23.8" flat-screen IPS monitor with an attractive three-sided ultrathin bezel design that helps you get the most out of your flexible work style. Enjoy vivid, realistic picture quality thanks to enhanced Full HD (1920 x 1080) resolution, paired with 300-nit brightness and generous 178/178° wide viewing angles. This model features built-in 2W + 2W speakers to let you enjoy the media whenever you need. Monitor 24P3CV is ready to boost your productivity with USB-C supporting Power Delivery up to 65W, data transfer and DP-alt mode. Connectivity of this monitor is enhanced with USB Hub, RJ-45 & DP-out. Keeping sustainability in mind, an array of environmental certifications including EPA, TCO, and EPEAT complete this monitor.

GENERAL	
Model Name	24P3CV
Channel	B2B
Product line	Pro-line
Design family	P3
Launch date (ETA)	2/14/2023

SCREEN	
Screen size (inch)	23.8
Screen size (cm)	60.5
Flat / Curved	Flat
Display hardness	3H
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	IPS
Backlight type	WLED
Max Refresh rate	75 Hz
Response time GtG	4 ms
Static contrast ratio	1000:1
Dynamic contrast ratio	50M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0.2745
Pixels per Inch	93

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100x100
Tilt	-5/35
Swivel	180°
Pivot	-90°~90°
Height adjust (mm)	150mm

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.4 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	✓
USB Hub speed	USB 3.2
USB downstream ports	4
RJ45	1x 10M/100M/1G
DisplayPort output	1x DP-Out 1.2

MULTIMEDIA

Speakers	✓
Speaker power	2 W x 2
Audio Output	1x Audio out

FEATURES

Sync technology (VRR)	Adaptive Sync
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	✓
Colour space (sRGB) CIE 1976 %	124.3
Colour space (DCI-P3) CIE 1976 %	93.9

SUSTAINABILITY

TCO Certified	9
Energy star	Energy star 8
EPEAT	Silver

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3
Energy class	E

PRODUCT DIMENSIONS (METRIC)

Product dimensions incl. base (WxHxD) mm	540(W)x (384.4-502.9)(H)x 200.1(D)
Product dimensions excl. base (WxHxD) mm	540(W)x 326.3(H)x 50.7(D)
Packaging dimensions (WxHxD) mm	613 (W) x 519 (H) x 162 (D)
Gross weight incl. package (in kg)	8.31
Product with stand (kg)	5.37
Product without stand (kg)	3.66

WHAT'S IN THE BOX

HDMI cable	1.8
Displayport cable	1.8
USB-C to C/A cable	1.8
Power Cable	✓
Power cable C13	1.8

OTHER INFORMATION

MTBF	70.000 hours (excluded backlight) + 30.000 hours (including backlight)
MTBF (excluding panel)	70.000 hours
MTBF (including panel)	30.000 hours