



22B2DM

Modern and sleek 21.5" 3-sides borderless monitor with Full HD and eye-caring LowBlue and FlickerFree technology

Modernized design and crisp Full HD images. The 22B2DM combines a sleek 3-sides frameless panel and HDMI connectivity. Enjoy working or streaming with wide viewing angles and eyesoothing LowBlue and FlickerFree technologies.

GENERAL	
Model Name	22B2DM
Channel	B2C
Product line	Basic-line
Design family	B2
Launch date (ETA)	6/15/2021

SCREEN	
Screen size (inch)	21.5
Screen size (cm)	54.61
Flat / Curved	Flat
Display hardness	3H
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	75 Hz
Response time GtG	4 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2482

1/3



EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100×100
Tilt	-5/21,5
Pivot	No

CONNECTIVITY AND MULTIMEDIA	
НДМІ	HDMI 1.4 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x
DVI	1x DVI-D

MULTIMEDIA	
Speakers	-
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES	
Sync technology (VRR)	Adaptive Sync
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	✓

SUSTAINABILITY	
Energy star	Energy star 8

2/3



POWER / ENVIRONMENTAL	
Power supply	External
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.3
Power consumption off in watts	0.3
Energy class	E

PRODUCT DIMENSIONS (METRIC)	
Product dimensions incl. base (WxHxD) mm	388.11(H) x 492.78(W) x 162.94(D)
Product dimensions excl. base (WxHxD) mm	292.68(H) x 492.78(W) x 36.2(D)
Packaging dimensions (WxHxD) mm	370(H) x 550(W) x 120(D)
Gross weight incl. package (in kg)	3.5
Product with stand (kg)	2.1

WHAT'S IN THE BOX	
HDMI cable	1.5
Power cable C13	1.5

REGULATORY COMPLIANCE	
ISO 9241-307	/