



24B2XHM2

Thin and sleek 23.8" VA monitor with lively colours, wide angle visibility and eye-friendly technology

The 24B2XHM2 from the B2 Series employs a 23.8" Full HD VA panel offering wide viewing angles, accurate and lively colours plus flexible connectivity. It features a slim profile and a 3-sides borderless panel for seamless multi monitor setups. Say goodbye to eyestrain thanks to AOC's LowBlue and FlickerFree technologies.

GENERAL	
Model Name	24B2XHM2
Channel	B2C
Product line	Basic-line
Design family	B2
Launch date (ETA)	1/15/2021

SCREEN	
Screen size (inch)	23.8
Screen size (cm)	60.452
Flat / Curved	Flat
Display hardness	зн
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	75 Hz
Response time GtG	4 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2745
Pixels per Inch	93

1/3



EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100x100
Tilt	-5/21.5
Pivot	No

CONNECTIVITY AND MULTIMEDIA	
HDMI	HDMI 1.4 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x

MULTIMEDIA	
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES	
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	/

POWER / ENVIRONMENTAL	
Power supply	External
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.3
Power consumption off in watts	0.3
Energy class	E

2/3



PRODUCT DIMENSIONS (METRIC)	
Product dimensions incl. base (WxHxD) mm	418.35(H) x 539.47(W) x 170.94(D)
Product dimensions excl. base (WxHxD) mm	320.94(H) x 539.47(W) x 37.6(D)
Packaging dimensions (WxHxD) mm	492(H) x 614(W) x 131(D)
Gross weight incl. package (in kg)	4.5
Product with stand (kg)	2.7

WHAT'S IN THE BOX	
HDMI cable	1.8
Power cable C13	1.8

OTHER INFORMATION	
MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE	
ISO 9241-307	✓