

TEST REPORT

Product Name: LCD Monitor

Trade Mark: AOC

Model No.: Q24G4E

Add. Model No.: **Q24G4*****

Report Number: 24040910655EMC-1

Test Standards:

EN 55032:2015, EN 55032:2015/A11:2020, EN 55032:2015/A1:2020,
CISPR 32:2015+AMD1:2019,
BS EN 55032:2015, BS EN 55032:2015+A1:2020, BS EN 55032:2015+A11:2020,
AS/NZS CISPR 32:2015+A1:2020, EN 55035:2017, EN 55035:2017/A11:2020,
BS EN 55035:2017, BS EN 55035:2017+A11:2020, CISPR 35:2016,
EN 61000-3-2:2014, EN IEC 61000-3-2:2019/A1:2021,
BS EN 61000-3-2:2014, BS EN IEC 61000-3-2:2019+A1:2021,
EN 61000-3-3:2013, EN 61000-3-3:2013/A1:2019, EN 61000-3-3:2013/A2:2021,
BS EN 61000-3-3:2013, BS EN 61000-3-3:2013+A1:2019, BS EN 61000-3-3:2013+A2:2021,
(IEC 61000-4-2:2008, IEC 61000-4-3:2020, IEC 61000-4-4:2012,
IEC 61000-4-5:2014+AMD1:2017, IEC 61000-4-6:2013, IEC 61000-4-8:2009,
IEC 61000-4-11:2020/COR2:2022)

Test Result: PASS

Date of Issue: May 22, 2024

Prepared for:

TPV Electronics (Fujian) Co., Ltd.

**Rongqiao Economic and Technological Development Zone, Fuqing
City, Fujian Province, P.R. China**

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China**

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen
Senior Project Engineer

Reviewed by:

Robben Chen

Robben Chen
Assistant Manager

Approved by:

Billy Li

Billy Li
Technical Director

Date:

May 22, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Version

Version No.	Date	Description
V1.0	May 22, 2024	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	5
1.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	6
1.4 DESCRIPTION OF SUPPORT UNITS	6
1.5 TEST LOCATION	6
1.6 TEST FACILITY	7
1.7 DEVIATION FROM STANDARDS	7
1.8 ABNORMALITIES FROM STANDARD CONDITIONS	7
1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
1.10 MEASUREMENT UNCERTAINTY	8
2. TEST SUMMARY	9
3. EQUIPMENT LIST	11
4. TEST CONFIGURATION	14
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	14
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	14
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	14
4.2 TEST MODES	15
5. PERFORMANCE CRITERIA	16
5.1 For EN 55035:2017/A11:2020	16
6. EMC REQUIREMENTS SPECIFICATION	17
6.1 REFERENCE DOCUMENTS FOR TESTING	17
6.2 EMC EMISSION	18
6.2.1 RADIATED EMISSION	18
6.2.2 CONDUCTED EMISSION (AC MAINS POWER PORTS)	25
6.2.3 HARMONIC CURRENT EMISSIONS	28
6.2.4 VOLTAGE FLUCTUATIONS AND FLICKER	32
6.3 IMMUNITY (ENCLOSURE PORTS)	33
6.3.1 RF ELECTROMAGNETIC FIELD	33
6.3.2 ELECTROSTATIC DISCHARGE	35
6.3.3 POWER FREQUENCY MAGNETIC FIELD	37
6.4 IMMUNITY (AC MAINS POWER PORTS)	39
6.4.1 ELECTRICAL FAST TRANSIENTS/BURST	39
6.4.2 CONTINUOUS INDUCED RF DISTURBANCES	41
6.4.3 VOLTAGE DIPS AND VOLTAGE INTERRUPTIONS	43
6.4.4 SURGES	45
7. PHOTOGRAPHS OF TEST SETUP	47
8. PHOTOGRAPHS OF EUT	53

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	TPV Electronics (Fujian) Co., Ltd.
Address of Applicant:	Rongqiao Economic and Technological Development Zone, Fuqing City, Fujian Province, P.R. China

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	LCD Monitor
Model No.:	Q24G4E
Add. Model No.:	**Q24G4*****
Trade Mark:	AOC
Rated Voltage:	100-240V~50/60Hz 1.5A
Classification of MME:	Class B
Highest Internal Frequency:	720 MHz
I/O Port:	1 x AC input Port; 1 x HDMI input Ports; 1 x DP Port; 1 x Audio Out Port;
Sample Received Date :	April 7, 2024
Sample Tested Date :	April 14, 2024 to April 29, 2024
Note: The additional model **Q24G4***** is identical with the test model Q24G4E except the model number for marketing purpose.	

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

HDMI Cable	
Description:	HDMI Cable
Cable Type:	Shielded without ferrite
Length:	1.5/1.8Meter

DP Cable	
Description:	DP Cable
Cable Type:	Shielded without ferrite
Length:	1.5/1.8Meter

AC Power Cord	
Description:	AC Power Cord
Cable Type:	Unshielded without ferrite
Length:	1.5/1.8Meter

Audio Out Port	
Description:	Audio Out Port
Cable Type:	Unshielded without ferrite
Length:	1.5/1.8Meter

1.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a LCD Monitor, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

EN 55032:2015, EN 55032:2015/A11:2020, EN 55032:2015/A1:2020,
CISPR 32:2015+AMD1:2019,
BS EN 55032:2015, BS EN 55032:2015+A1:2020, BS EN 55032:2015+A11:2020,
AS/NZS CISPR 32:2015+A1:2020, EN 55035:2017, EN 55035:2017/A11:2020,
BS EN 55035:2017, BS EN 55035:2017+A11:2020, CISPR 35:2016,
EN 61000-3-2:2014, EN IEC 61000-3-2:2019/A1:2021,
BS EN 61000-3-2:2014, BS EN IEC 61000-3-2:2019+A1:2021,
EN 61000-3-3:2013, EN 61000-3-3:2013/A1:2019, EN 61000-3-3:2013/A2:2021,
BS EN 61000-3-3:2013, BS EN 61000-3-3:2013+A1:2019, BS EN 61000-3-3:2013+A2:2021,
(IEC 61000-4-2:2008, IEC 61000-4-3:2020, IEC 61000-4-4:2012,
IEC 61000-4-5:2014+AMD1:2017, IEC 61000-4-6:2013, IEC 61000-4-8:2009,
IEC 61000-4-11:2020/COR2:2022)

All test items have been performed and recorded as per the above standards

1.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Serial Number	Supplied by
PC	DELL	XPS8900	2015AP3055	UnionTrust
keyboard	DELL	KB212-B	CN-0N291F-715	UnionTrust
mouse	DELL	MS111	CN-011D3V-738	UnionTrust
DVD Player	GIEC	BDP-G4305	N/A	UnionTrust
PC work station	DELL	5820	BEC20190001	UnionTrust
Earphone	N/A	QTER01JY	N/A	UnionTrust
Dummy load	N/A	E214887	N/A	UnionTrust

1.5 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

Tests were sub-contracted. [Power frequency magnetic field]

GRG Metrology & Test Group Co., Ltd.

Address: No. 1301 Guanguang Road, Xinlan Community, Guanlan Street, Longhua District, Shenzhen, 518110, People's Republic of China

Telephone: 86-028-86496515

Tests were sub-contracted. [Radiated Emission (10 m)]

Shenzhen Academy of Metrology & Quality Inspection

Address: Songshahu Lab ,No.7 of Industrial North Road, Songshan Lake Hi-Tech Industrial Zone, Dongguan, Guangdong, People's Republic of China

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

1.6 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

➤ **Shenzhen UnionTrust Quality and Technology Co., Ltd.**

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories. (This standard version IEC 61000-4-11:2020/COR2:2022 is not within the scope of UnionTrust CNAS authorization)

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

➤ **GRG Metrology & Test Group Co., Ltd.**

A2LA-Lab Certificate No.: 2861.01

CNAS-Lab Code: L0446

➤ **Shenzhen Academy of Metrology & Quality Inspection.**

CNAS-Lab Code: L0579

1.7 DEVIATION FROM STANDARDS

None.

1.8 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.10 MEASUREMENT UNCERTAINTY

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	± 3.2 dB
2	Conducted emission 150kHz-30MHz	± 2.7 dB
3	Radiated emission 30MHz-1GHz	± 4.6 dB
4	Radiated emission 1GHz-18GHz	± 4.4 dB
5	Harmonic current emissions	$\pm 1.4\%$
6	Voltage fluctuations and flicker	$\pm 1.4\%$
Remark: 95% Confidence Levels, k=2.		

2. TEST SUMMARY

Test Item		Test Requirement	Test Method	Limits	Results
Radiated Emissions	for class A equipment	EN 55032:2015/A1 1:2020 Clause 5	EN 55032:2015/A1 1:2020 Clause 6	Table A2, A3	N/A (Note 1, 2)
	for class B equipment			Table A4, A5	PASS
	for FM receivers			Table A6	N/A (Note 1, 3)
	for outdoor units of home satellite receiving systems			Table A7	N/A (Note 1, 4)
Conducted Emissions	for conducted emissions from the AC mains power ports of Class A equipment	EN 55032:2015/A1 1:2020 Clause 5	EN 55032:2015/A1 1:2020 Clause 6	Table A9	N/A (Note 1, 2)
	for conducted emissions from the AC mains power ports of Class B equipment			Table A10	PASS
	for asymmetric mode conducted emissions from Class A equipment			Table A11	N/A (Note 1, 2)
	for asymmetric mode conducted emissions from Class B equipment			Table A12	N/A (Note 1, 5)
	for conducted differential voltage emissions from Class B equipment			Table A13	N/A (Note 1, 6)
Harmonic Current Emissions		EN IEC 61000-3-2: 2019/A1:2021 Clause 6	EN IEC 61000-3-2: 2019/A1:2021 Clause 6	EN IEC 61000-3-2: 2019/A1:2021 Clause 7	PASS
Voltage Fluctuations and Flicker		EN 61000-3-3: 2013/A2:2021 Clause 4	EN 61000-3-3: 2013/A2:2021 Clause 4	EN 61000-3-3: 2013/A2:2021 Clause 5	PASS

Note:

- 1) N/A: In the whole report not application.
- 2) The EUT is Class B equipment.
- 3) Applicable only to FM receivers, the EUT does not support FM receivers.
- 4) The EUT not belong to satellite receiving systems.
- 5) The cables used in this EUT are all less than 3 meters.
- 6) The EUT does not support the TV broadcast receiver tuner ports with an accessible connector, RF modulator output ports and FM broadcast receiver tuner ports with an accessible connector.

➤ For EN 55035:2017/A11:2020

Part 1: Immunity requirements for enclosure ports			
Test Item	Test Requirement (EN 55035:2017/A11:2020)	Test Method	Results
Power frequency magnetic field	Table Clause 1.1	IEC 61000-4-8:2009	PASS
Continuous RF electromagnetic field disturbances, swept test and spot test	Table Clause 1.2 Table Clause 1.3	IEC 61000-4-3:2020	PASS
Electrostatic Discharge (ESD)	Table Clause 1.4	IEC 61000-4-2:2008	PASS

Part 2: Immunity requirements for AC mains power ports			
Test Item	Test Requirement (EN 55035:2017/A11:2020)	Test Method	Results
Continuous induced RF disturbances	Table Clause 4.1	IEC 61000-4-6:2013	PASS
Voltage dips and Voltage interruptions	Table Clause 4.2 Table Clause 4.3	IEC 61000-4-11:2020/COR2:2022	PASS
Surges	Table Clause 4.4	IEC 61000-4-5:2014+AMD1:2017	PASS
Electrical fast transients/burst	Table Clause 4.5	IEC 61000-4-4:2012	PASS

Part 3: Immunity requirements for DC network power ports			
Test Item	Test Requirement (EN 55035:2017/A11:2020)	Test Method	Results
Continuous induced RF disturbances	Table Clause 3.1	IEC 61000-4-6:2013	N/A (Note 1, 2)
Surges	Table Clause 3.2	IEC 61000-4-5:2014+AMD1:2017	N/A (Note 1, 2)
Electrical fast transients/burst	Table Clause 3.3	IEC 61000-4-4:2012	N/A (Note 1, 2)

Note:

- 1) N/A: In this whole report not application.
- 2) This EUT does not support the DC wired network ports capability.

Part 4: Immunity requirements for analogue/digital data ports			
Test Item	Test Requirement (EN 55035:2017/A11:2020)	Test Method	Results
Continuous induced RF disturbances	Table Clause 2.1	IEC 61000-4-6:2013	N/A (Note 1, 3)
Broadband impulse noise disturbances, repetitive	Table Clause 2.2	EN 55035:2017/A11:2020 Clause 4.2.7	N/A (Note 1, 2)
Broadband impulse noise disturbances, isolated	Table Clause 2.3	EN 55035:2017/A11:2020 Clause 4.2.7	N/A (Note 1, 2)
Surges	Table Clause 2.4	IEC 61000-4-5:2014+AMD1:2017	N/A (Note 1, 3)
Electrical fast transients/burst	Table Clause 2.5	IEC 61000-4-4:2012	N/A (Note 1, 3)

Note:

- 1) N/A: In this whole report not application.
- 2) Applicable only to CPE xDSL ports, all burst durations. This EUT does not support the ports capability.
- 3) The cables used in this EUT are all less than 3 meters.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

3. EQUIPMENT LIST

Radiated Emission (3m) Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
<input checked="" type="checkbox"/>	Receiver	R&S	ESIB26	100114	27-Oct-2023	26-Oct-2024
<input type="checkbox"/>	Broadband Antenna	ETS-LINDGREN	3142E	00201566	30-Oct-2023	29-Oct-2024
<input type="checkbox"/>	6dB Attenuator	Talent	RA6A5-N-18	18103001	30-Oct-2023	29-Oct-2024
<input type="checkbox"/>	Preamplifier	HP	8447F	2805A02960	31-Oct-2023	30-Oct-2024
<input checked="" type="checkbox"/>	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	1-Apr-2023	31-Mar-2025
<input checked="" type="checkbox"/>	Pre-amplifier	ETS-LINDGREN	00118385	00201874	1-Apr-2023	31-Mar-2025
<input checked="" type="checkbox"/>	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	LISN	R&S	ESH2-Z5	860014/024	27-Oct-2023	26-Oct-2024
<input checked="" type="checkbox"/>	LISN	ETS-Lindgren	3816/2SH	00201088	27-Oct-2023	26-Oct-2024
<input checked="" type="checkbox"/>	Receiver	R&S	ESR7	101181	27-Oct-2023	26-Oct-2024
<input checked="" type="checkbox"/>	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	27-Oct-2023	26-Oct-2024
<input type="checkbox"/>	ISN	Schwarzbeck	NTFM 8158	NTFM 8158 0113	27-Oct-2023	26-Oct-2024
<input checked="" type="checkbox"/>	Test Software	EZ-EMC	EZ-CON	Software Version: EMC-CON 3A1.1		

Harmonic Current Emissions & Voltage Fluctuations and Flicker Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	5KVA AC POWER SOURCE	California instruments	5001iX+CT S-411	56178	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Flicker & Harmonic Tester	California instruments	PACS-1	72333	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Test Software	California instruments	CTS 4	Software Version: 4.29.0		

Electrostatic Discharge Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	ESD Simulator	TESEQ	NSG438	634	3-Nov-2023	2-Nov-2024

Fast transients common mode & Surges Test (AC Port)						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	NSG 3040 EMC test system	TESEQ	NSG 3040	2101	31-Oct-2023	30-Oct-2024
<input checked="" type="checkbox"/>	Capacitive coupling clamp	HTEC	H3C	155103	29-Dec-2023	28-Dec-2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

RF common mode 0.15 MHz to 80 MHz Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	Conducted Immunity System	Schloder	CDG 6000-75	126B1367	27-Oct-2023	26-Oct-2024
<input checked="" type="checkbox"/>	Coupling/Decoupling network	Schloder	CDN M2+M3-16	A2210363	31-Oct-2023	30-Oct-2024
<input checked="" type="checkbox"/>	6dB Attenuator	Schloder	CDG60100	201411010018	31-Oct-2023	30-Oct-2024
<input checked="" type="checkbox"/>	EM-Clamp	Schloder	EMCL-20	132A1245	31-Oct-2023	30-Oct-2024
<input checked="" type="checkbox"/>	Audio Test System	Audio Precision	ATS-1	ATS1-41075	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Test Software	Dr. Hubert GmbH	IEC/EN610 00-4-6	Software Version: 1.2.0(25.03.2013)		
<input checked="" type="checkbox"/>	Test Software	HTEC	CS5045	Software Version: 2.01		

Voltage dips and interruptions Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	Voltage dips and variation test system	NTEC	HPFS 161P	161503	31-Oct-2023	30-Oct-2024
<input checked="" type="checkbox"/>	Voltage Interruption Simulator with Step Simulator	NTEC	HV1P16	161504	31-Oct-2023	30-Oct-2024

RF electromagnetic field Test						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
<input checked="" type="checkbox"/>	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-C T001270-1317	11-Nov-2023	10-Nov-2026
<input checked="" type="checkbox"/>	Audio Test System	Audio Precision	ATS-1	ATS1-41075	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Log Periodic Antenna	Schwarzbeck	VUSLP 9111E	00041	17-Apr-2024	16-Apr-2025
<input checked="" type="checkbox"/>	Stacked Logarithmic-Periodic Broadband Antenna	Schwarzbeck	STLP 9149	00706	17-Apr-2024	16-Apr-2025
<input checked="" type="checkbox"/>	Electric field probe	Frankonia	EFS-100	711ZX00424	2-Apr-2024	1-Apr-2025
<input checked="" type="checkbox"/>	RF Amplifier	HTEC	HPA 0810-250	MPA2003056	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	RF Amplifier	HTEC	HPA 1060-75	MPA2003057	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Audio conditioner	HTEC	PM_AB T/C35	2020051002	29-Oct-2023	26-Oct-2024
<input checked="" type="checkbox"/>	Microphone	HTEC	FFMP_AB T/C35	2020051001	01-Nov-2023	31-Oct-2024
<input checked="" type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	MY47070613	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	EPM-P Series Power Meter	Agilent	E4417A	MY45100705	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Peak and Avg Power Sensor	Agilent	E9323A	MY44420776	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Peak and Avg Power Sensor	Agilent	E9323A	US40410105	29-Mar-2024	28-Mar-2025
<input checked="" type="checkbox"/>	Shielding box	SKET	ABSB_AB T/C35	N/A	N/A	N/A
<input checked="" type="checkbox"/>	Test Software	Suzhou Keleto Electronics Technology Co.,Ltd	EMC-S	Software Version: V1.4.0.57		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

PFMF Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. Due date	Cal. Interval
<input checked="" type="checkbox"/>	Power supply	SCHAFFNER	NSG1007	54789	Nov. 17, 2024	1 year
<input checked="" type="checkbox"/>	PFMF Generator	SCHAFFNER	INA2141	6003	Jul. 14, 2024	1 year
<input checked="" type="checkbox"/>	PFMF Magnetic antenna	SCHAFFNER	INA-702	711-1115	Jul. 14, 2024	1 year
<input checked="" type="checkbox"/>	Test software	TESEQ	Win2120	Software Version: Ver6.00		

Radiated Emission (10m SAC) Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. Due date	Cal. Interval
<input checked="" type="checkbox"/>	10m SAC	Albatross Projects	10m SAC	SB19656	2025-08-28	3 year
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESI26	SB3436	2024-10-12	1 year
<input checked="" type="checkbox"/>	Antenna	Schwarzbeck	VULB9163	SB19658/01	2024-07-23	1 year
<input checked="" type="checkbox"/>	Test Software	Tonscend	JS32-RE	Software Version: Ver.5.0.5		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage	Relative Humidity (%)
NT/NV	+15 to +35	1. 110~60Hz 2. 230~50Hz	20 to 75 (Except Electrostatic Discharge is 30 to 60)
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Radiated Emission(3m)	24.2	56.9	99.8	S202404073074-ZJA01/1	Bowie Zhang
Radiated Emission(10m)	22.5	51.9	101		Shuifu You
Conducted Emission	24.0	56.6	99.9		Linson Xie
Harmonic Current Emissions& Voltage Fluctuations and Flicker	25	66	100		Lucas Ouyang
RF electromagnetic field	23.9	56.3	100.1		Yana Zeng
Electrostatic Discharge	23.5	57.5	100.1		Lucas Ouyang
Fast transients, common mode	25	66	100		
RF common mode 0.15 MHz to 80 MHz					
Voltage dips and interruptions					
Surges	25.1	63.6	100.1		
Power frequency magnetic field	26.8	59	100.2		

4.2 TEST MODES

Test Modes									
No.	Test Voltage	Input ports	Input source	Cable Length (Meter)	Pattern	Resolution	Rotatio	Stand Position	Audio
1	230V~50Hz	HDMI 1	PC	1.8	H Pattern	800*600@60Hz	Landscape	UP	With Earphone
2			PC	1.8	H Pattern	1920*1080@60Hz	Landscape	UP	With Earphone
3			PC	1.8	H Pattern	2560*1440@60Hz	Landscape	UP	With Earphone
4			PC	1.8	H Pattern	2560*1440@180Hz	Landscape	UP	With Earphone
5			PC	1.8	BT 471-1	2560*1440@180Hz	Landscape	UP	Without Earphone
6*			PC	1.8	BT 471-1	2560*1440@180Hz	Landscape	UP	With Earphone
7			PC	1.5	H Pattern	2560*1440@180Hz	Landscape	UP	Without Earphone
8			DVD	1.8	BT 471-1	--	Landscape	UP	With Earphone
9			DVD	1.5	BT 471-1	--	Landscape	UP	Without Earphone
10		DP 1	PC	1.8	BT 471-1	800*600@60Hz	Landscape	UP	With Earphone
11			PC	1.8	BT 471-1	1920*1080@60Hz	Landscape	UP	With Earphone
12			PC	1.8	BT 471-1	2560*1440@60Hz	Landscape	UP	With Earphone
13			PC	1.8	BT 471-1	2560*1440@180Hz	Landscape	UP	With Earphone
14			PC	1.5	BT 471-1	2560*1440@180Hz	Landscape	UP	Without Earphone
15	Worst case from Test mode 1~14 with 1.5m Power Cord						Landscape	Down	With Earphone
16	110V~60Hz	Worst case from Test mode 1~15							
Note:									
1) "*"Means the worst test mode.									
2) All test modes are performed at maximum brightness, contrast, and volume.									

5. PERFORMANCE CRITERIA

5.1 FOR EN 55035:2017/A11:2020

➤ <General>

General performance criteria are defined in 8.2, 8.3 and 8.4. These criteria shall be used during the testing of primary functions where no relevant annex is applicable.

When assessing the impact of a disturbance on a function, the assessment should take into consideration the function's performance prior to the application of the disturbance and only identify as failures those changes in performance that are a result of the disturbance.

➤ <Performance criterion A>

The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

➤ <Performance criterion B>

During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.

After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.

If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

➤ <Performance criterion C>

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.

Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

➤ PERFORMANCE CRITERION FOR OTHERS FUNCTION

Function	Performance criterion
Broadcast reception function	Refer to Annex A.4 of EN 55035:2017/A11:2020
Print function	Refer to Annex B.3 of EN 55035:2017/A11:2020
Scan function	Refer to Annex C.3 of EN 55035:2017/A11:2020
Display and display output functions	Refer to Annex D.3 of EN 55035:2017/A11:2020
Musical tone generating function	Refer to Annex E.3 of EN 55035:2017/A11:2020
Networking functions	Refer to Annex F.3.3 & F.4 of EN 55035:2017/A11:2020
Audio output function	Refer to Annex G.7 of EN 55035:2017/A11:2020
Telephony function	Refer to Annex H.7 of EN 55035:2017/A11:2020

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

6. EMC REQUIREMENTS SPECIFICATION

6.1 REFERENCE DOCUMENTS FOR TESTING

**EN 61000-3-2:2014, EN IEC 61000-3-2:2019/A1:2021,
BS EN 61000-3-2:2014, BS EN IEC 61000-3-2:2019+A1:2021,**
Electromagnetic compatibility (EMC) Part 3-2: Limits — Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)

**EN 61000-3-3:2013, EN 61000-3-3:2013/A1:2019, EN 61000-3-3:2013/A2:2021,
BS EN 61000-3-3:2013, BS EN 61000-3-3:2013+A1:2019, BS EN 61000-3-3:2013+A2:2021,**
Electromagnetic compatibility (EMC) Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection

**EN 55032:2015, EN 55032:2015/A11:2020, EN 55032:2015/A1:2020,
CISPR 32:2015+AMD1:2019, AS/NZS CISPR 32:2015+A1:2020,
BS EN 55032:2015, BS EN 55032:2015+A1:2020, BS EN 55032:2015+A11:2020**
Electromagnetic compatibility of multimedia equipment - Emission Requirements

**EN 55035:2017, EN 55035:2017/A11:2020,
BS EN 55035:2017, BS EN 55035:2017+A11:2020, CISPR 35:2016,**
Electromagnetic compatibility of multimedia equipment - Immunity requirements

IEC 61000-4-2:2008
Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test

IEC 61000-4-3:2020
Electromagnetic compatibility (EMC) - Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test

IEC 61000-4-4:2012
Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test

IEC 61000-4-5:2014+AMD1:2017
Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test

IEC 61000-4-6:2013
Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields

IEC 61000-4-8:2009
Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test

IEC 61000-4-11:2020
Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests

6.2 EMC EMISSION

6.2.1 Radiated Emission

Test Requirement: EN 55032:2015/A11:2020 Clause 5

Test Method: EN 55032:2015/A11:2020 Clause 6

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Table 1 – Required highest frequency for radiated measurement	
Highest internal frequency (Fx)	Highest measured frequency
$F_x \leq 108\text{ MHz}$	1 GHz
$108\text{ MHz} < F_x \leq 500\text{ MHz}$	2 GHz
$500\text{ MHz} < F_x \leq 1\text{ GHz}$	5 GHz
$F_x > 1\text{ GHz}$	$5 \times F_x$ up to a maximum of 6 GHz
NOTE 1 For FM and TV broadcast receivers, F_x is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.	
NOTE 2 F_x is defined in 3.1.18.	
NOTE 3 For outdoor units of home satellite receiving systems highest measured frequency shall be 18 GHz.	

Limit:

Class B

Table A.4 – Requirements for radiated emissions at frequencies up to 1 GHz for class B equipment

Table clause	Frequency range (MHz)	Measurement receiver bandwidth			Class B limits dB(μV/m)
		Facility (see Table A.1)	Distance m	Detector type / bandwidth	
A4.1	30 to 230	OATS/SAC	10	Quasi Peak / 120 kHz	30
	230 to 1 000				37
A4.2	30 to 230	OATS/SAC	3		40
	230 to 1 000				47
A4.3	30 to 230	FAR	10	Quasi Peak / 120 kHz	32 to 25
	230 to 1 000				32
A4.4	30 to 230	FAR	3		42 to 35
	230 to 1 000				42
Apply only table clause A4.1 or A4.2 or A4.3 or A4.4 across the entire frequency range. These requirements are not applicable to the local oscillator and harmonics frequencies of equipment covered by Table A.6.					

Table A.5 – Requirements for radiated emissions at frequencies above 1 GHz for class B equipment

Table clause	Frequency range (MHz)	Measurement receiver bandwidth			Class B limits dB(μV/m)
		Facility (see Table A.1)	Distance m	Detector type / bandwidth	
A5.1	1 000 to 3 000	FSOATS	3	Average / 1 MHz	50
	3 000 to 6 000				54
A5.2	1 000 to 3 000			Peak / 1 MHz	70
	3 000 to 6 000				74
Apply A5.1 and A5.2 across the frequency range from 1 000 MHz to the highest required frequency of measurement derived from Table 1.					

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Test setup for radiated emissions of tabletop equipment






Figure 2. Above 1 GHz

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- 1) The radiated emissions were tested in a semi-anechoic chamber.
- 2) The Product was placed on the non-conductive turntable 0.8 m or 0.1 m above the ground at a chamber.
- 3) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 4) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:

- 1) The radiated emissions were tested in a fully Anechoic Chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:

Below 1GHz(Quasi Peak): 10 Meter test distance

Test Mode 6

Horizontal



◆ QP Detector

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	64.990	6.4	12.16	18.5	30.00	-11.5	Peak
2	152.465	9.5	8.89	18.4	30.00	-11.6	Peak
3	214.669	8.6	12.19	20.8	30.00	-9.2	Peak
4	366.293	9.3	16.14	25.5	37.00	-11.5	Peak
5	657.876	10.6	21.17	31.8	37.00	-5.2	Peak
6	710.361	9.2	21.73	30.9	37.00	-6.1	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2


Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	66.934	9.6	11.51	21.1	30.00	-8.9	Peak
2	152.465	15.7	8.89	24.6	30.00	-5.4	Peak
3	212.725	10.3	12.05	22.4	30.00	-7.6	Peak
4	241.884	11.8	13.33	25.1	37.00	-11.9	Peak
5	342.966	9.2	15.99	25.2	37.00	-11.8	Peak
6	584.008	5.0	20.22	25.2	37.00	-11.8	Peak

Remark: The testing of Radiated Emissions @10 Meter test distance was performed in Shenzhen Academy of Metrology & Quality Inspection.

Above 1GHz(Peak & Average)
Test Mode 6
Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1200.965	35.44	-12.44	23.00	50.00	-27.00	Average
2	1200.965	48.57	-12.44	36.13	70.00	-33.87	Peak
3	1583.456	29.68	-11.16	18.52	50.00	-31.48	Average
4	1583.456	47.87	-11.16	36.71	70.00	-33.29	Peak
5	2401.590	33.22	-7.52	25.70	50.00	-24.30	Average
6	2401.590	49.39	-7.52	41.87	70.00	-28.13	Peak
7	3317.773	27.36	-4.51	22.85	54.00	-31.15	Average
8	3317.773	45.54	-4.51	41.03	74.00	-32.97	Peak
9	4327.568	26.68	-1.35	25.33	54.00	-28.67	Average
10	4327.568	42.85	-1.35	41.50	74.00	-32.50	Peak
11	5050.089	25.14	-0.54	24.60	54.00	-29.40	Average
12	5050.089	43.32	-0.54	42.78	74.00	-31.22	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
1	1029.142	35.67	-12.92	22.75	50.00	-27.25	Average
2	1029.142	49.82	-12.92	36.90	70.00	-33.10	Peak
3	1500.426	32.76	-11.32	21.44	50.00	-28.56	Average
4	1500.426	48.92	-11.32	37.60	70.00	-32.40	Peak
5	2401.590	27.21	-7.52	19.69	50.00	-30.31	Average
6	2401.590	46.41	-7.52	38.89	70.00	-31.11	Peak
7	3513.965	24.41	-3.55	20.86	54.00	-33.14	Average
8	3513.965	43.60	-3.55	40.05	74.00	-33.95	Peak
9	4599.960	25.26	-1.12	24.14	54.00	-29.86	Average
10	4599.960	41.42	-1.12	40.30	74.00	-33.70	Peak
11	5406.647	25.52	0.42	25.94	54.00	-28.06	Average
12	5406.647	41.69	0.42	42.11	74.00	-31.89	Peak

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 230V~50Hz and 110V~60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

6.2.2 Conducted Emission (AC mains power ports)

Test Requirement: EN 55032:2015/A11:2020 Clause 5

Test Method: EN 55032:2015/A11:2020 Clause 6

Limit:


Class B

Table A.10 – Requirements for conducted emissions from the AC mains power ports of Class B equipment

Table clause	Frequency range (MHz)	Coupling device (see Table A.8)	Detector type / bandwidth	Class B limits dB(μV)
A10.1	0.15 to 0.5	AMN	Quasi Peak / 9 kHz	66 to 56
	0.5 to 5			56
	5 to 30			60
A10.1	0.15 to 0.5	AMN	Average / 9 kHz	56 to 46
	0.5 to 5			46
	5 to 30			50
Apply A10.1 and A10.2 across the entire frequency range.				

Test Setup:

Test setup for conducted emissions of tabletop equipment



Test Procedures:

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The table top EUT was placed upon a non-metallic table 0.8 m or 0.1 m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m or 0.1 m from the boundary of the unit under test

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The worst measurement data as follows:

Quasi Peak and Average:


Test Mode6

Live Line



No.	Frequency (MHz)	Reading dB(μV)	Correction factor (dB)	Result dB(μV)	Limit dB(μV)	Margin (dB)	Remark
1	0.1500	40.85	10.20	51.05	66.00	-14.95	QP
2	0.1500	23.71	10.20	33.91	56.00	-22.09	AVG
3	0.1770	37.05	10.18	47.23	64.63	-17.40	QP
4	0.1770	25.70	10.18	35.88	54.63	-18.75	AVG
5	0.2490	29.06	10.19	39.25	61.79	-22.54	QP
6	0.2490	16.83	10.19	27.02	51.79	-24.77	AVG
7	2.3235	18.99	10.24	29.23	56.00	-26.77	QP
8	2.3235	7.95	10.24	18.19	46.00	-27.81	AVG
9	19.1084	22.01	10.74	32.75	60.00	-27.25	QP
10	19.1084	20.10	10.74	30.84	50.00	-19.16	AVG
11	20.4404	25.22	10.80	36.02	60.00	-23.98	QP
12	20.4404	22.60	10.80	33.40	50.00	-16.60	AVG

Neutral Line



No.	Frequency (MHz)	Reading dB(μV)	Correction factor (dB)	Result dB(μV)	Limit dB(μV)	Margin (dB)	Remark
1	0.1500	44.68	10.19	54.87	66.00	-11.13	QP
2	0.1500	33.41	10.19	43.60	56.00	-12.40	AVG
3	0.1860	35.75	10.08	45.83	64.21	-18.38	QP
4	0.1860	26.40	10.08	36.48	54.21	-17.73	AVG
5	0.2085	33.26	10.05	43.31	63.26	-19.95	QP
6	0.2085	24.75	10.05	34.80	53.26	-18.46	AVG
7	0.3840	23.46	10.17	33.63	58.19	-24.56	QP
8	0.3840	16.37	10.17	26.54	48.19	-21.65	AVG
9	3.8445	21.33	10.25	31.58	56.00	-24.42	QP
10	3.8445	15.27	10.25	25.52	46.00	-20.48	AVG
11	20.4404	25.42	10.75	36.17	60.00	-23.83	QP
12	20.4404	23.02	10.75	33.77	50.00	-16.23	AVG

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 230V~50Hz and 110V~60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-EMC-EN55032-V1.2

6.2.3 Harmonic Current Emissions

Test Requirement: EN IEC 61000-3-2:2019/A1:2021 Clause 6

Test Method: The appropriate requirements of EN 61000-3-2/A1 for harmonic current emission apply for equipment covered by the scope of the present document with an input current up to and including 16A per phase. For equipment with an input current of greater than 16A per phase EN 61000-3-12 applies.

Test Setup:



Equipment Used: Refer to section 3 for details.

Test Result: pass

The worst measurement data as follows:


Harmonics – Class-D per IEC 61000-3-2:2018/AMD1:2020(Run time)

EUT: Q24G4E
Test category: Class-D (European limits)
Test date: 2024/4/14
Test duration (min): 2.5
Comment: Mode 6
Customer: 24040910655


Tested by: Lucas
Test Margin: 100
Start time: 10:35:10
End time: 10:37:52
Data file name: H-000315.cts_data

Test Result: N/L Source qualification: Normal

Current & voltage waveforms



Harmonics and Class D limit line European Limits



Test result: N/L Worst harmonics H0-0.0% of 150% limit, H0-0% of 100% limit

Current Test Result Summary (Run time)

EUT: Q24G4E
Test category: Class-D (European limits)
Test date: 2024/4/14
Test duration (min): 2.5
Comment: Mode 6
Customer: 24040910655

Tested by: Lucas
Test Margin: 100
Start time: 10:35:10
End time: 10:37:52
Data file name: H-000315.cts_data

Test Result: N/L
Source qualification: Normal
THC(A): 0.152 I-THD(%): 171.9 POHC(A): 0.019 POHC Limit(A): 0.008

Highest parameter values during test:

V_RMS (Volts): 230.44
I_RMS (Amps): 0.729
L_Fund (Amps): 0.088
Power (Watts): 18.8
Frequency(Hz): 50.00
I_RMS (Amps): 0.184
Crest Factor: 4.072
Power Factor: 0.448

Harm#	Harms(ava)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.001	0.000	N/A	0.001	0.000	N/A	N/L
3	0.074	0.064	N/A	0.079	0.096	N/A	N/L
4	0.001	0.000	N/A	0.001	0.000	N/A	N/L
5	0.070	0.036	N/A	0.074	0.053	N/A	N/L
6	0.000	0.000	N/A	0.001	0.000	N/A	N/L
7	0.064	0.019	N/A	0.067	0.028	N/A	N/L
8	0.000	0.000	N/A	0.000	0.000	N/A	N/L
9	0.056	0.009	N/A	0.059	0.014	N/A	N/L
10	0.000	0.000	N/A	0.000	0.000	N/A	N/L
11	0.047	0.007	N/A	0.049	0.010	N/A	N/L
12	0.000	0.000	N/A	0.000	0.000	N/A	N/L
13	0.038	0.006	N/A	0.039	0.008	N/A	N/L
14	0.000	0.000	N/A	0.000	0.000	N/A	N/L
15	0.029	0.005	N/A	0.029	0.007	N/A	N/L
16	0.000	0.000	N/A	0.000	0.000	N/A	N/L
17	0.021	0.004	N/A	0.021	0.006	N/A	N/L
18	0.000	0.000	N/A	0.000	0.000	N/A	N/L
19	0.014	0.004	N/A	0.014	0.006	N/A	N/L
20	0.000	0.000	N/A	0.000	0.000	N/A	N/L
21	0.009	0.003	N/A	0.009	0.005	N/A	N/L
22	0.000	0.000	N/A	0.000	0.000	N/A	N/L
23	0.006	0.003	N/A	0.007	0.005	N/A	N/L
24	0.000	0.000	N/A	0.000	0.000	N/A	N/L
25	0.007	0.003	N/A	0.007	0.004	N/A	N/L
26	0.000	0.000	N/A	0.000	0.000	N/A	N/L
27	0.007	0.003	N/A	0.008	0.004	N/A	N/L
28	0.000	0.000	N/A	0.000	0.000	N/A	N/L
29	0.008	0.002	N/A	0.008	0.004	N/A	N/L
30	0.000	0.000	N/A	0.000	0.000	N/A	N/L
31	0.007	0.002	N/A	0.007	0.003	N/A	N/L
32	0.000	0.000	N/A	0.000	0.000	N/A	N/L
33	0.006	0.002	N/A	0.006	0.003	N/A	N/L
34	0.000	0.000	N/A	0.000	0.000	N/A	N/L
35	0.004	0.002	N/A	0.004	0.003	N/A	N/L
36	0.000	0.000	N/A	0.000	0.000	N/A	N/L
37	0.003	0.002	N/A	0.003	0.003	N/A	N/L
38	0.000	0.000	N/A	0.000	0.000	N/A	N/L
39	0.002	0.002	N/A	0.002	0.003	N/A	N/L
40	0.000	0.000	N/A	0.000	0.000	N/A	N/L

Note: The EUT power level is below 75.0 Watts and therefore has no defined limits.

Voltage Source Verification Data (Run time)

EUT: Q24G4E
Test category: Class-D (European limits)
Test date: 2024/4/14
Test duration (min): 2.5
Comment: Mode 6.
Customer: 24040910655.
Tested by: Lucas.
Test Margin: 100.
Start time: 10:35:10
End time: 10:37:52.
Data file name: H-000315.cts_data.

Test Result: N/L Source qualification: Normal.

Highest parameter values during test:

Voltage (V_{rms}): 230.44
Peak (Amps): 0.729
Fund (Amps): 0.088
Power (Watts): 18.8
Frequency(Hz): 50.00.
I_{RMS} (Amps): 0.184.
Crest Factor: 4.072.
Power Factor: 0.448.


Harm#	Harmonics V _{rms}	Limit V _{rms}	% of Limit	Status
2	0.137	0.461	29.66	OK
3	0.638	2.073	30.77	OK
4	0.074	0.461	15.99	OK
5	0.025	0.922	2.77	OK
6	0.032	0.461	6.92	OK
7	0.048	0.691	6.88	OK
8	0.028	0.461	6.15	OK
9	0.024	0.461	5.17	OK
10	0.025	0.461	5.52	OK
11	0.038	0.230	16.71	OK
12	0.017	0.230	7.41	OK
13	0.023	0.230	10.08	OK
14	0.017	0.230	7.33	OK
15	0.030	0.230	12.96	OK
16	0.022	0.230	9.67	OK
17	0.011	0.230	4.79	OK
18	0.023	0.230	9.96	OK
19	0.017	0.230	7.40	OK
20	0.019	0.230	8.35	OK
21	0.008	0.230	3.67	OK
22	0.013	0.230	5.47	OK
23	0.008	0.230	3.56	OK
24	0.006	0.230	2.65	OK
25	0.014	0.230	6.02	OK
26	0.009	0.230	4.03	OK
27	0.006	0.230	2.68	OK
28	0.007	0.230	2.99	OK
29	0.014	0.230	6.04	OK
30	0.009	0.230	3.74	OK
31	0.008	0.230	3.52	OK
32	0.009	0.230	3.69	OK
33	0.014	0.230	6.19	OK
34	0.007	0.230	2.95	OK
35	0.008	0.230	3.51	OK
36	0.006	0.230	2.65	OK
37	0.005	0.230	2.32	OK
38	0.005	0.230	2.08	OK
39	0.007	0.230	3.00	OK
40	0.006	0.230	2.64	OK

6.2.4 Voltage Fluctuations and Flicker

Test Requirement: EN 61000-3-3:2013/A2:2021 Clause 4

Test Method: The appropriate requirements of EN 61000-3-3 for voltage fluctuations and flicker apply for equipment covered by the scope of the present document with an input current up to and including 16A per phase, if no conditional connection is needed. Where a conditional connection is required then the requirements of EN 61000-3-11 [12] shall apply.
For equipment with an input current of greater than 16A up to and including 75A per phase EN 61000-3-11 applies.

Test Setup:




Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows: Test Mode 6

Flicker Test Summary per EN/IEC61000-3-3 Ed. 3.0 (2013) (Run time)

	Result	Test Limit
dt > 3.3 % (ms)	0	500.0
dc (%)	0.00	3.30
dmax (%)	0.00	4.00
Pst (10 min. period)	0.291	1.000
Pit (2 hr. period)	N/A	0.650



6.3 IMMUNITY (ENCLOSURE PORTS)

6.3.1 RF electromagnetic field

Test Requirement:	EN 55035:2017/A11:2020 Table Clause 1.2, Table Clause 1.3
Test Method:	The test method shall be in accordance with EN 61000-4-3
Criterion Required:	performance criteria A
Frequency range:	swept test: 80 MHz to 1 000 MHz spot test: 1 800 MHz, 2 600 MHz, 3 500 MHz, 5 000 MHz
Test Level:	Level 2: 3 V/m(measured unmodulated)
Modulation:	1 kHz Sine wave, 80 % Amp. Modulation, audio signal of 400 Hz
Frequency Step:	1 % increment
Dwell time:	1 seconds
Polarity Antenna:	Horizontal and vertical

Test Setup:

Test setup for Continuous RF electromagnetic field disturbances, swept test and spot test of tabletop equipment




Figure 1. 80 MHz to 1 GHz





Figure 2. Above 1 GHz

Test setup for acoustic measurements



Test Procedures:

- 1) For table-top equipment, the EUT was placed in the chamber on a non-conductive table 0.8m high. For arrangement of floor-standing equipment, the EUT was mounted on a non-conductive support 0.1m above the supporting plane. For human body-mounted equipment, the EUT may be tested in the same manner as table top items.
- 2) If possible, a minimum of 1 m of cable is exposed to the electromagnetic field. Excess length of cables interconnecting units of the EUT shall be bundled low-inductively in the approximate center of the cable to form a bundle 30 cm to 40 cm in length.
- 3) The EUT was initially placed with one face coincident with the calibration plane. The EUT face being illuminated was contained within the UFA (Uniform Field Area).
- 4) The frequency ranges to be considered were swept with the signal modulated and pausing to adjust the RF signal level or to switch oscillators and antennas as necessary. Where the frequency range was swept incrementally, the step size was not exceed 10 % of the preceding frequency value.
- 5) The dwell time of the amplitude modulated carrier at each frequency was not be less than the time necessary for the EUT to be exercised and to respond, and was not less than 0.5 s.
- 6) The test normally was performed with the generating antenna facing each side of the EUT.
- 7) The polarization of the field generated by each antenna necessitates testing each selected side twice, once with the antenna positioned vertically and again with the antenna positioned horizontally.
- 8) The EUT was performed in a configuration to actual installation conditions, a video camera and/or an audio monitor were used to monitor the performance of the EUT.

Equipment Used: Refer to section 3 for details.

Test Result: See below table.

EUT Face	Frequency	Level	Result (Pursuant to EN 55035 Criterion A)
Front	Swept test: 80 MHz to 1 000 MHz Spot test: 1.8 GHz, 2.6 GHz, 3.5 GHz, 5.0 GHz	3 V/m	A
Back			A
Left			A
Right			A
Top			A
Under			A

Observation:

- ☐ No observable change.
- ☒ The audio output signal level was monitored during test and was found to be at least 20dB less than the reference level recorded before the start of the test.


Conclusion: The EUT met the requirements of the standard.

6.3.2 Electrostatic Discharge

Test Requirement:	EN 55035:2017/A11:2020 Table Clause 1.4
Test Method:	The test method shall be in accordance with EN 61000-4-2
Criterion Required:	performance criteria B
Discharge Impedance:	330 Ω / 150 pF
Polarity:	Positive & Negative
Number of Discharge:	Minimum 10 times at each test point
Discharge Mode:	Single Discharge
Discharge Period:	1 second minimum
Test Level:	Contact discharge: Level 2, ± 4 kV Air discharge: Level 3, ± 8 kV

Test Setup:

Test set-up for table-top equipment



IEC 2209/08

Test Procedures:

- Electrostatic discharges shall be applied only to points and surfaces of the EUT which are expected to be touched during normal operation, including user access operations specified in the user manual, for example cleaning or adding consumables when the EUT is powered. The application of discharges to the contacts of open connectors is not required.
When applying direct discharges to a portable or handheld battery- powered EUT with a display screen, it may not be possible to observe the screen for a given EUT orientation. If observation of the screen is necessary during this test, the EUT may be mounted vertically using non - metallic supports.
- The EUT was put on a 0.8m high wooden table for table-top equipment or 0.1m high for floor standing equipment standing on the ground reference plane (GRP).

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

- 3) A horizontal coupling plane(HCP) 1.6m by 0.8m in size was placed on the table, and the EUT with its cables were isolated from the HCP by an insulating support thick than 0.5mm. The VCP 0.5m by 0.5m in size & HCP were constructed from the same material type & think mess as that of the GRP, and connected to the GRP via a 470kΩ resistor at each end. The distance between EUT and any of the other metallic surface excepted the GRP, HCP and VCP was greater than 1m.
- 4) During the contact discharges, the tip of the discharge electrode was touch the EUT before the discharge switch is operated. During the air discharges, the round discharge tip of the discharge electrode was approached as fast as possible to touch the EUT.
- 5) After each discharge, the ESD generator was removed from the EUT, the generator was then retriggered for a new single discharge. For ungrounded product, a discharge cable with two resistances was used after each discharge to remove remnant electrostatic voltage. 10 times of each polarity single discharge were applied to HCP and VCP.

Equipment Used: Refer to section 3 for details.


Test Result: See below table.

Discharge Type	Applied Voltage	Pulse No.	Result (Pursuant to EN55035 Criterion B)		
Contact Discharge	± 4 kV	10 for every level	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)	<input type="checkbox"/> N/A
Air Discharge	± 8 kV	10 for every level	<input type="checkbox"/> A	<input checked="" type="checkbox"/> B (see phenomena)	<input type="checkbox"/> N/A
Indirect HCP Discharge	± 4 kV	10 for every level	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)	<input type="checkbox"/> N/A
Indirect VCP Discharge	± 4 kV	10 for every level	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)	<input type="checkbox"/> N/A
Remark: N/A: Not applicable					
Observation: <input type="checkbox"/> No observable change. <input checked="" type="checkbox"/> During the experiment, the following phenomena occurred: 1. During the test, Air Discharge on the Screen edge, the EUT screen flashes. After the test is automatically restored.					
Conclusion: The EUT met the requirements of the standard.					

6.3.3 Power frequency magnetic field

Test Requirement:	EN 55035:2017/A11:2020 Table Clause 1.1
Test Method:	The test method shall be in accordance with IEC 61000-4-8
Criterion Required:	A
Frequency:	50 or 60
Test Level:	Level 2: 1 A/m (rms)
Test Setup:	


Test setup for floor-standing equipment



Components

GRP	Ground plane	C1	Power supply circuit
A	Safety earth	C2	Signal circuit
S	Insulating support	L	Communication line
EUT	Equipment under test	B	To power supply source
Ic	Inductive coil	D	To signal source, simulator
E	Earth terminal	G	To the test generator

Test set-up for table-top equipment



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Test Procedures:

- 1) The Product and support units were located on a table, 0.8m away from ground floor.
- 2) The Product is configured and connected to satisfy its functional requirements. It shall be place on the GRP with the interposition of a 0.1m thickness insulating support (e.g. dry wood)
- 3) Setting the parameter of tests and then perform the test software of test simulator.
- 4) The induction coil shall enclose the Product placed at its centre.

Equipment Used: Refer to section 3 for details.

Test Result: See below table.

Direction	Field Strength (A/m)	Duration (Min)	Result (Pursuant to EN55035 Criterion A)
X axis	1	1	A
Y axis	1	1	A
Z axis	1	1	A

Observation: No observable change.

Conclusion: The EUT met the requirements of the standard.

Remark: The testing of Power frequency magnetic field was performed in GRG Metrology & Test Group Co., Ltd.

6.4 IMMUNITY (AC MAINS POWER PORTS)

6.4.1 Electrical fast transients/burst

Test Requirement: EN 55035:2017/A11:2020 Table Clause 4.5

Test Method: The test method shall be in accordance with EN 61000-4-4

Criterion Required: performance criteria B

Test Port : AC mains power port

Polarity: Positive & Negative

Test Level and Repetition Frequency:

- The test level for AC mains power input ports shall be 1 kV (Test Level: 2) open circuit voltage at a repetition rate of 5 kHz as given EN 61000-4-4.

Impulse Wave shape: 5/50 ns


Burst Duration: 15ms

Burst Period: 300ms

Test Duration: 2 minute per level & polarity

Test Setup:

Test set-up for table-top equipment



IEC 645/12

(A) location for supply line coupling

(B) location for signal lines coupling

Test Procedures:

- 1) The EUT was placed on a ground reference plane (GRP) insulated by an insulating support 0.1m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
- 2) The GRP shall project beyond the EUT and the clamp by at least 0.1m on all sides. The distance between the EUT and any other of the metallic surface except the GRP was greater than 0.5m. All cables to the EUT was placed on the insulation support 0.1m above GRP. A cable not subject to EFT was routed as far as possible from cable under test to minimize the coupling between the cables.
- 3) The length of signal and power cable between the EUT and EFT generator was 0.5m. If the cable is a non-detachable supply cable more than 0.5m, the excess length of this cable shall be folded to avoid a flat coil and situated at a distance of 0.1m above the GRP.
- 4) The EUT was conducted the below specified test voltages for line and neutral or line, neutral and earth simultaneously (for Wired network, single, control and DC port line with capacitive coupling clamp), 120 seconds duration. If the equipment contains identical ports, only one was tested; multicomputer cables, such as a 50-pair Wired network cable, were tested as a single cable. Cables did not be split or divided into groups of conductors for this test; interface ports, which were intended by the manufacturer to be connected to data cables not longer than 3 m, did not be tested.


Equipment Used: Refer to section 3 for details.

Test Result: See below table.

Test Ports	Test Level	Result	
		(Pursuant to EN 55035 Criterion B)	
AC mains power ports	$\pm 0.5 \text{ kV}, \pm 1.0 \text{ kV}$	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)
Observation: <input checked="" type="checkbox"/> No observable change. <input type="checkbox"/> During the experiment, the following phenomena occurred:			
Conclusion: The EUT met the requirements of the standard.			


6.4.2 Continuous induced RF disturbances

Test Requirement:	EN 55035:2017/A11:2020 Table Clause 4.1
Test Method:	The test method shall be in accordance with EN 61000-4-6
Criterion Required:	performance criteria A
Test Level:	0.15 MHz to 10 MHz: 3 V (r.m.s) 10 MHz to 30 MHz: 3 to 1 V (r.m.s) 30 MHz to 80 MHz: 1 V (r.m.s)
Modulation:	80%, 1kHz Amplitude Modulation
Step Size:	1% increment
Dwell Time:	1s
Test Setup:	



Schematic setup for immunity test used for CDN

Test setup for acoustic measurements



Test Procedures:

- 1) The Product and support units were located at a ground reference plane with the interposition of a 0.1 m thickness insulating support and the CDN was located on GRP directly.
- 2) The frequency range is swept from 150 kHz to 80MHz, with the signal 80% amplitude modulated with a 1 kHz sine wave. The rate of sweep did not exceed 1.5×10^{-3} decade/s. Where the frequency range is swept incrementally, the step size was 1% of fundamental.
- 1) The dwell time at each frequency shall be not less than the time necessary for the Product to be able to respond.

Equipment Used: Refer to section 3 for details.

Test Result: See below table.

Test Ports	Frequency	Test Level	Result (Pursuant to EN 55035 Criterion A)
AC mains power ports	0.15 MHz to 10 MHz	3 V	A
	10 MHz to 30 MHz	3 to 1 V	A
	30 MHz to 80 MHz	1 V	A
Observation: <input type="checkbox"/> No observable change. <input checked="" type="checkbox"/> The audio output signal level was monitored during test and was found to be at least 20dB less than the reference level recorded before the start of the test. Conclusion: The EUT met the requirements of the standard.			

6.4.3 Voltage dips and Voltage interruptions

Test Requirement: EN 55035:2017/A11:2020 Table Clause 4.2/ 4.3

Test Method: The test method shall be in accordance with EN 61000-4-11

Criterion Required:

Voltage dips	performance criteria B or C
interruptions	performance criteria C

Test Port : AC mains power port

>95 % reduction: 0,5 period

Test Level: >30 % reduction: 25 period for 50Hz / 30 period for 60Hz


>95 % reduction: 250 period for 50Hz / 300 period for 60Hz

No. of Dips / Interruptions: 3 per Level

Interval between Event: Minimum 10 seconds

Phase Angle: 0°/45°/90°/135°/180°/225°/270°/315°

Test Setup:



Test Procedures:

- 1) The EUT was placed on a ground reference plane (GRP) insulated by an insulating support 0.1 m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
- 2) The test was performed with the EUT connected to the test generator with the shortest power supply cable as specified by the EUT manufacturer.
- 3) The EUT was tested for each selected combination of test level and duration with a sequence of three dips /interruptions with intervals of 10 s minimum. Each representative mode of operation was tested.
- 4) For EUT with more than one power cord, each power cord was tested individually.

Equipment Used: Refer to section 3 for details.

Test Result: See below table.

Test Condition		Result (Pursuant to EN 55035 Criterion B or C)			
Test Level in %UT	Period	Meet Criterion B		Meet Criterion C	
0	0.5	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)	N/A	
70	25 for 50 Hz 30 for 60 Hz	N/A		<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena) <input type="checkbox"/> C(see phenomena)
0	250 for 50 Hz 300 for 60 Hz	N/A		<input type="checkbox"/> A	<input checked="" type="checkbox"/> B (see phenomena) <input type="checkbox"/> C(see phenomena)
Remark: N/A: Not applicable					
Observation: <input type="checkbox"/> No observable change. <input checked="" type="checkbox"/> During the experiment, the following phenomena occurred: <u>The EUT turned off at 0%UT test level with 250/300 cycles (at 230V~50Hz/110V~60Hz) duration and it could auto resume to normal after the test.</u>					
Conclusion: The EUT met the requirements of the standard.					

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

6.4.4 Surges

Test Requirement:	EN 55035:2017/A11:2020 Table Clause 4.4
Test Method:	The test method shall be in accordance with EN 61000-4-5
Criterion Required:	performance criteria B
Wave Shape:	for AC mains power and DC network power ports 1.2/50 (8/20) μ s
Test Level:	for AC mains power ports: 2 kV line to ground, and 1 kV line to line
Polarity:	Positive & Negative
Interval:	60s between each surge
No. of Surges:	5 positive at 90°, 5 negative at 270°
Test Setup:	




Figure 1. For AC port

Test Procedures:

Test Procedure:

- 1) The EUT was placed on a ground reference plane (GRP) insulated by an insulating support 0.1 m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
- 2) The 1.2/50 μ s surge was to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks were required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines and to provide sufficient decoupling impedance to the surge wave so that the specified wave may be applied on the lines under test.
- 3) The power cord between the EUT and the coupling/decoupling network was not exceed 2 m in length. The interconnection line between the EUT and the coupling/decoupling network shall not exceed 2 m in length.
- 4) The EUT was conducted 0.5 kV and 1 kV test voltage for line to line and line to neutral and conducted 0.5 kV, 1 kV and 2 kV test voltage for line to earth and neutral to earth, five positive pulses and five negative pulses each at 90°, 270° for a.c. power ports and five positive pulses and five negative surge pulses for d.c. power ports, The test levels were applied on the EUT with a 2 Ω generator source impedance for power supply terminals and 12 Ω output impedance for interconnection lines. The tests were done at repetition rate one per minute.

Equipment Used: Refer to section 3 for details.

Test Result: See below table.

For AC mains power port			
Test Ports	Level	Result (Pursuant to EN 55035 Criterion B)	
Line to line	± 1.0 kV	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)
Lines to ground	± 2.0 kV	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B (see phenomena)
Remark: N/A: Not applicable			
Observation: <input checked="" type="checkbox"/> No observable change. <input type="checkbox"/> During the experiment, the following phenomena occurred:			
Conclusion: The EUT met the requirements of the standard.			

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-EMC-EN55032-V1.2

7. PHOTOGRAPHS OF TEST SETUP

Radiated emission Test Setup (30MHz~1GHz)_ 10 Meter test distance



Radiated emission Test Setup (Above 1GHz)



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com


<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Conducted Emission (AC port) Test Setup



Harmonic & Flicker Test Setup



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Electrostatic Discharge Test Setup



Fast Transients, Common mode / Surge Test Setup (AC Port) Test Setup



RF electromagnetic field Test Setup



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

Radio frequency, common mode (AC Port) Test Setup



Power frequency magnetic field Test Setup



Voltage dips and interruptions Test Setup



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

8. PHOTOGRAPHS OF EUT



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-EN55032-V1.2

EUT Photo



EUT Photo



*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
