

Find your product and get support

FAQ

Driver

User Manual

Europe

<https://aoc.com/uk/support>

Asia

<https://aoc.com/ru/support>

Australia

https://au.aoc.com/user_manual

Hong Kong S.A.R.

https://hk.aoc.com/user_manual

中國台灣

https://tw.aoc.com/user_manual

Indonesia

https://id.aoc.com/user_manual

日本

https://jp.aoc.com/user_manual

한국

https://kr.aoc.com/user_manual

Malaysia

https://my.aoc.com/user_manual

Myanmar

https://mm.aoc.com/user_manual

New Zealand

https://nz.aoc.com/user_manual

Philippines

https://ph.aoc.com/user_manual

Singapore

https://sg.aoc.com/user_manual

ประเทศไทย

https://th.aoc.com/user_manual

Việt Nam

https://vn.aoc.com/user_manual

Middle East

https://me.aoc.com/user_manual

South Africa

https://za.aoc.com/user_manual

Brasil

<https://aoc.portaltpv.com.br/>

India

<https://aoc.com/in-en/support>

US

<https://aoc.com/us/support>

Canada

<https://aoc.com/ca-en/support>

HDMI

HIGH-DEFINITION MULTIMEDIA INTERFACE

Product information for EU/UK Energy

H41 G24M261593A

AOC GAMING

QUICK START GUIDE

24G4HRE

AOC GAMING MONITOR

©2025 AOC. All rights reserved

WWW.AOC.COM

Monitor

Stand

Base

Quick Start Guide

Warranty Card

Power Cable

HDMI Cable

DisplayPort Cable

*Different according to countries/regions

Display design may differ from that illustrated

1

2

3

4

General Specification			
Panel	Model Name	24G4HRE	
	Driving System	TFT Color LCD	
	Viewable Image Size	60.5cm Diagonal (23.8" Wide Screen)	
	Pixel Pitch	0.2745mm(H)x0.2745mm(V)	
Others	Horizontal Scan Range	30k-230kHz	
	Horizontal Scan Size(Maximum)	527.04mm	
	Vertical Scan Range	48-200Hz	
	Vertical Scan Size(Maximum)	296.46mm	
	Max Resolution	1920x1080@200Hz	
	Plug & Play	VESA DDC2B/C1	
	Power Source	100-240V- 50/60Hz 1.5A	
	Power Consumption	Typical(Default Brightness And Contrast)	19W
		Max. (Brightness = 100, Contrast =100)	≤ 42W
		Standby Mode	≤ 0.3W
Physical Characteristics	Dimensions(with stand)	540.0x434.5x177.39mm (WxHxD)	
	Net Weight	3.43kg	
	Connector Type	HDMIx2/DisplayPort/Earphone Out	
Environmental	Signal Cable Type	Detachable	
	Built-In Speaker	2Wx2	
	Temperature	Operating	0°C-40°C