

Find your product and get support

FAQ

Driver

User Manual

Europe

<https://aoc.com/uk/support>

Россия

<https://aoc.com/ru/support>

Australia

https://au.aoc.com/user_manual

Hong Kong S.A.R.

https://hk.aoc.com/user_manual

中國台灣

https://tw.aoc.com/user_manual

Indonesia

https://id.aoc.com/user_manual

日本

https://jp.aoc.com/user_manual

한국

https://kr.aoc.com/user_manual

Malaysia

https://my.aoc.com/user_manual

Myanmar

https://mm.aoc.com/user_manual

New Zealand

https://nz.aoc.com/user_manual

Philippines

https://ph.aoc.com/user_manual

Singapore

https://sg.aoc.com/user_manual

ประเทศไทย

https://th.aoc.com/user_manual

Việt Nam

https://vn.aoc.com/user_manual

Middle East

https://me.aoc.com/user_manual

South Africa

https://za.aoc.com/user_manual

Brasil

<https://aoc.portaltpv.com.br/>

India

<https://aoc.com/in-en/support>

US

<https://aoc.com/us/support>

Canada

<https://aoc.com/ca-en/support>



Product information for EU/UK Energy




XXXXXXXXXXXX

AOC





Quick Start Guide
U27B3A

www.aoc.com
©2024 AOC.All Rights Reserved






*Different according to countries/regions
Display design may differ from that illustrated


1



2



3



4

General Specification

Panel	Model name	U27B3A	
	Driving system	TFT Color LCD	
	Viewable Image Size	68.5cm diagonal (27" Wide Screen)	
	Pixel pitch	0.1554mm(H) x 0.1554mm(V)	
Others	Horizontal scan range	30k-140KHz	
	Horizontal scan Size(Maximum)	596.736mm	
	Vertical scan range	40-60Hz	
	Vertical Scan Size(Maximum)	335.664mm	
	Optimal preset resolution	3840×2160@60Hz	
	Plug & Play	VESA DDC2B/CI	
	Power Source	100-240V~ 50/60Hz 1.5A	
	Power Consumption	Typical (default brightness and contrast) Max. (brightness =100, contrast =100) Standby mode	27W ≤ 52W ≤ 0.5W
Physical Characteristics	Dimensions(with stand)	614.0x460.0x229.8mm (WxHxD)	
	Net Weight	4.04kg	
	Connector Type	HDMIx2/DP/Earphone	
	Signal Cable Type	Detachable	
Environmental	Built-In Speaker	2Wx2	
	Temperature	Operating	0°C~ 40°C
		Non-Operating	-25°C~ 55°C
	Humidity	Operating	10% ~ 85% (non-condensing)
		Non-Operating	5% ~ 93% (non-condensing)
	Altitude	Operating	0m~5000m(0ft~16404ft)
		Non-Operating	0m~12192m(0ft~40000ft)