U2879VF



28" 4K monitor with FreeSync and 1 ms response time

With DisplayPort 1.2a, HDMI 2.0, a 1 ms response time and FreeSync support, this 4K display is ready for super-smooth entertainment content at 60 frames per second.



Features



UHD (4K) Resolution 4K Ultra High-Definition (3840 x 2160) resolution delivers ultra-crisp picture quality and allows users to see more on the screen at one time. This provides more screen 'real estate' and shows more detail for sharper and more brilliant images. Whether working on the next beautiful photo, or design, or even just used for productivity, users will marvel at the true, crisp image that only a UHD display can provide.



Display Port

DisplayPort offers ultra-fast digital audio and video transmission without quality loss or input lag. Quickly and easily connect a range of devices to your screen, including your computer, laptop, media player, game console and more. It's perfect for professionals as well as the most demanding home users.



Freesync

The AMD FreeSync Technology ensures that the GPU's and monitor's refresh rates are synchronised, which provides a smooth, tear free gaming experience. You will appreciate the low input lag if you're looking for the best quality visuals in fast paced games.

GENERAL	
Model Name	U2879VF
EAN	4038986185714
Channel	B2C
Product line	Value-line
Design family	79 ID
Launch date (ETA)	2/27/2016

EXTERIOR	
Bezel type (front)	Narrow
Bezel Colour (front)	Black
Bezel finishing (front)	Glossy
Cabinet colour (backside)	Silver, Black
Cabinet finishing (backside)	Glossy

ERGONOMICS	
Tilt	-5/24
Pivot	No

SUSTAINABILITY		
TCO Certified	6	

FEATURES	
Sync technology (VRR)	Freesync
Flicker-Free	Flicker Free

SCREEN	
Screen size (inch)	28,0
Screen size (cm)	71,12
Flat / Curved	Flat
Display hardness	3H
Panel resolution	3840x2160
Resolution name	UHD
Aspect ratio	16:9
Panel type	TN
Backlight type	WLED
Backlight type Max Refresh rate	WLED 60 Hz
Max Refresh rate	60 Hz
Max Refresh rate Response time GtG	60 Hz 1 ms
Max Refresh rate Response time GtG Static contrast ratio Dynamic contrast	60 Hz 1 ms 1000:1
Max Refresh rate Response time GtG Static contrast ratio Dynamic contrast ratio	60 Hz 1 ms 1000:1 80M:1
Max Refresh rate Response time GtG Static contrast ratio Dynamic contrast ratio Viewing angle (CR10)	60 Hz 1 ms 1000:1 80M:1 170/160

POWER / ENVIRONMENTAL	
Power supply	External
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0,32
Power consumption off in watts	0,23
Energy class	F

WHAT'S IN THE BOX	
HDMI cable	1.8
Displayport cable	1.8

CONNECTIVITY AND MULTIMEDIA		
Audio Output	Headphone out (3.5mm)	

PRODUCT DIMENSIONS	
Product dimensions incl. base (WxHxD) mm	468.4(H) × 659.3(W) x 153.2(D)
Packaging dimensions (WxHxD) mm	543(H) × 732(W) x 159(D)
Gross weight incl. package (in kg)	5,26
Net weight excl. package (in kg)	4,0