

CU34P3CV

34 inch (86.36 cm) LCD MONITOR



The AOC CU34P3CV is a 34" WOH (3440 × 1440) curved VA screen with an attractive three-sided ultrathin bezel design that offers truly immersive viewing. This model's Wide QHD 21:9 aspect ratio expands your field of vision while providing a wrap-around view for an enhanced cinematic experience. The panel features 300-nit brightness and generous 178/178° wide viewing angles, along with two built-in 5W + 5W speakers to enhance your daily productivity in today's Wxible office. Monitor CU34P3CV is ready to boost your productivity with USB-C supporting Power Delivery up to 65W, data transfer and DP-alt mode. Connectivity of this monitor is enhanced with USB Hub and RJ-45. Keeping sustainability in mind, an array of environmental certifications including EPA, TCO, and EPEAT complete this monitor.

GENERAL

| | |
|---------------|---------------|
| Model Name | CU34P3CV |
| EAN | 4038986110730 |
| Channel | B2B |
| Product line | Pro-line |
| Design family | P3 |

| SCREEN | |
|------------------------|----------------|
| Screen size (inch) | 34 |
| Screen size (cm) | 86.36 |
| Flat / Curved | Curved |
| Curvature Radius | 1500R |
| Display hardness | 3H |
| Panel treatment | Antiglare (AG) |
| Panel resolution | 3440x1440 |
| Aspect ratio | 21:9 |
| Panel type | VA |
| Backlight type | WLED |
| Max Refresh rate | 100 Hz |
| Response time GtG | 4 ms |
| Static contrast ratio | 3000:1 |
| Dynamic contrast ratio | 20M:1 |
| Viewing angle (CR10) | 178/178 |
| Display colours | 16.7 Million |
| Brightness in nits | 300 cd/m2 |
| Pixel Pitch (mm) | 0.23175 |

| EXTERIOR | |
|------------------------------|-------------------|
| Bezel type (front) | 3-sided frameless |
| Bezel Colour (front) | Black |
| Bezel finishing (front) | Texture |
| Cabinet colour (backside) | Black |
| Cabinet finishing (backside) | Texture |

| ERGONOMICS | |
|--------------------|----------|
| Vesa wallmount | 100x100 |
| Tilt | -5~20° |
| Swivel | 175°±5 |
| Pivot | -90°~90° |
| Height adjust (mm) | 150mm |

CONNECTIVITY AND MULTIMEDIA

| | |
|----------------------|--|
| HDMI | HDMI 2.0 x 1 |
| DisplayPort | DisplayPort 1.4 x 1 |
| USB-C connectivity | USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W) |
| USB Hub | ✓ |
| USB Hub speed | USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit |
| USB downstream ports | 4 |
| RJ45 | 1x 10M/100M/1G |

MULTIMEDIA

| | |
|---------------|--------------|
| Speakers | ✓ |
| Speaker power | 5 W x 2 |
| Audio Output | 1x Audio out |

FEATURES

| | |
|----------------------|------------------------------------|
| Multiview (PbP, PiP) | PiP+PbP |
| Flicker-Free | Flicker Free |
| KVM | 1x USB3.2 Gen 2 type C + 1x type B |
| Kensington Lock | ✓ |

SUSTAINABILITY

| | |
|---------------|---------------|
| TCO Certified | 9 |
| Energy star | Energy star 8 |

POWER / ENVIRONMENTAL

| | |
|------------------------------------|--------------------|
| Power supply | Internal |
| Power source | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0.5 |
| Power consumption off in watts | 0.3 |

PRODUCT DIMENSIONS

| | |
|--|------------------------------------|
| Product dimensions incl. base (WxHxD) mm | 808.34 x (482.44-611.03) x275.13mm |
| Product dimensions excl. base (WxHxD) mm | 808.34 x 367.45 x 104.7mm |
| Packaging dimensions (WxHxD) mm | 1070(W) x 556(H) x 190(D) mm |
| Gross weight incl. package (in kg) | 12.95 |
| Net weight excl. package (in kg) | 10 |

WHAT'S IN THE BOX

| | |
|-----------------|-----|
| Power cable C13 | 1.8 |
|-----------------|-----|