



## CU34V5C/BK

34" VA WQHD panel for maximum productivity, with MultiView, USB-C and PD65W

The AOC CU34V5C is equipped with a 34" VA curved panel with Ultrawide QHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and height adjust as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.

GENERAL	
Model Name	CU34V5C/BK
Channel	B2C
Product line	Value-line
Design family	V5
Launch date (ETA)	7-18-2022

1/4



SCREEN	
Screen size (inch)	34
Screen size (cm)	86,4
Flat / Curved	Curved
Curvature Radius	1500R
Display hardness	6H
Panel treatment	Antiglare (AG)
Panel resolution	3440x1440
Resolution name	WQHD
Aspect ratio	21:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	100 Hz
Response time GtG	4 ms
Response time MPRT	1 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0,23175
Pixels per Inch	109,7

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Matt
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Matt

ERGONOMICS	
Vesa wallmount	100x100
Tilt	3° ±2° ~ 21° ±2°
Swivel	28° ±2° ~28° ±2°
Pivot	No
Height adjust (mm)	130mm



CONNECTIVITY AND MULTIMEDIA	
НДМІ	HDMI 2.0 x 1
Digital HDCP (HDMI version)	HDCP 2.2
DisplayPort	DisplayPort 1.2 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	/
USB Hub speed	USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit
USB downstream ports	4
USB fast charge port	/
RJ45	No
D-SUB (VGA)	0x
DVI	0x

MULTIMEDIA	
Speakers	✓
Speaker power	5 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)
MonitorWebcam	No

FEATURES	
Sync technology (VRR)	Freesync
Blue Light Technology	Low Blue Light
Multiview (PbP, PiP)	PbP, PiP
Flicker-Free	Flicker Free
KVM	No
Kensington Lock	/
Colour space (sRGB) CIE 1976 %	116
Colour space (DCI-P3) CIE 1931 %	90
Colour space (DCI-P3) CIE 1976 %	93
Colour space (Adobe RGB) CIE 1931 %	90
Colour space (Adobe RGB) CIE 1976 %	100



SUSTAINABILITY	
TCO Certified	No

POWER / ENVIRONMENTAL	
Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0,5
Power consumption off in watts	0,3
Energy class	G

PRODUCT DIMENSIONS	
Product dimensions incl. base (WxHxD) mm	808.1x(397.3~527.3)x250mm
Product dimensions excl. base (WxHxD) mm	808.1x365.3x99.9mm
Packaging dimensions (WxHxD) mm	1071x189x500mm
Gross weight incl. package (in kg)	11,75
Net weight excl. package (in kg)	9,34
Product without stand (kg)	6,76

WHAT'S IN THE BOX	
HDMI cable	1.5
USB-C to C cable	1.8
Power Cable	1

OTHER INFORMATION	
MTBF	50.000 hours (excluded backlight)
MTBF (including panel)	50.000 hours

4/4