

## Comfort, convenience, and performance in a 23.8" Full HD display with DisplayPort

The 24P2Q is equipped with a flat 23.8" IPS/3FL panel with Full HD resolution and 178°/178° wide viewing angles in a slim 3-sided frameless display. Designed to offer today's business the heightened productivity they seek, this model is compatible with VGA, DVI, HDMI, and DP and includes a USB 3.2 hub. Equipped with Low Blue Mode and Flicker-Free technology, it can be adjusted, tilted, pivoted, and swiveled to the ideal ergonomic position.



## **Features**



Full Ergonomics
Feel the comfort! AOC's height, tilt and swiveladjustable stands help you find the most comfortable and healthy position.



IPS Panel
IPS panel ensures an excellent viewing
experience with lifelike yet brilliant and accurate
colors. Colors look consistent no matter from
which angle you look at the display.



Frameless design
Besides looking modern and attractive,
frameless designs enable seamless multimonitor setups. Your cursor/windows will not be
lost anymore in the dark abyss of bezels, when
many displays are placed side by side.



TÜV Rheinland - Certified eye comfort
TÜV Rheinland - Certified eye comfort At AOC we
focus on eye protection and eye comfort, to reduce

focus on eye protection and eye comfort At ACC we focus on eye protection and eye comfort, to reduce negative symptoms such as eye strain, headaches and blurred vision. That's the reason why we cooperate with the national certification body (NCB) TÜV Rheinland, which acts both as a third-party testing and an eye comfort certification, in an impartial and independent way. This certification answers safety and quality standards demands by users, who are now so sure they have chosen the best product for their



Pivot function

Thanks to its pivot function, your monitor can be rotated by 180° from landscape into portrait mode, especially useful for desktop publishing.



## Speakers

Built-in speakers make it easy to catch up with family, friends and colleagues. For movies, music, games and more, you'll enjoy quality audio without the hassle of connecting external speakers.

| GENERAL           |               |
|-------------------|---------------|
| Model Name        | 24P2Q         |
| EAN               | 4038986147293 |
| Channel           | B2B           |
| Product line      | Pro-line      |
| Design family     | P2            |
| Launch date (ETA) | 7/1/2020      |

| EXTERIOR                     |                   |
|------------------------------|-------------------|
| Bezel type (front)           | 3-sided frameless |
| Bezel Colour (front)         | Black             |
| Bezel finishing (front)      | Texture           |
| Cabinet colour (backside)    | Black             |
| Cabinet finishing (backside) | Texture           |

| ERGONOMICS         |          |
|--------------------|----------|
| Vesa wallmount     | 100x100  |
| Tilt               | -5/35    |
| Swivel             | -180/180 |
| Pivot              | Yes      |
| Height adjust (mm) | 150mm    |
|                    |          |

| SUSTAINABILITY |               |
|----------------|---------------|
| TCO Certified  | 9             |
| Energy star    | Energy star 8 |

| FEATURES                               |                |
|--|----------------|
| Sync technology (VRR)                  | Adaptive Sync  |
| Blue Light<br>Technology               | Low Blue Light |
| Flicker-Free                           | Flicker Free   |
| Kensington Lock                        | Yes            |
| Colour space (Adobe<br>RGB) CIE 1931 % | 79,0           |

| SCREEN                 |                |
|------------------------|----------------|
| Screen size (inch)     | 23,8           |
| Screen size (cm)       | 60,452         |
| Flat / Curved          | Flat           |
| Display hardness       | 3H             |
| Panel treatment        | Antiglare (AG) |
| Panel resolution       | 1920x1080      |
| Resolution name        | FHD            |
| Aspect ratio           | 16:9           |
| Panel type             | IPS            |
| Backlight type         | WLED           |
| Max Refresh rate       | 75 Hz          |
| Response time GtG      | 4 ms           |
| Static contrast ratio  | 1000:1         |
| Dynamic contrast ratio | 50M:1          |
| Viewing angle (CR10)   | 178/178        |
| Display colours        | 16.7 Million   |
| Brightness in nits     | 300 cd/m2      |
| Pixel Pitch (mm)       | 0,2745         |
| Pixels per Inch        | 92,0           |

| POWER / ENVIRONMENTAL              |                    |
|------------------------------------|--------------------|
| Power supply                       | Internal           |
| Power source                       | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0,3                |
| Power consumption off in watts     | 0,3                |
| Energy class                       | D                  |

| WHAT'S IN THE I   | вох |
|-------------------|-----|
| HDMI cable        | 1.8 |
| Displayport cable | 1.8 |

| CONNECTIVITY AND MULTIMEDIA |  |
|-----------------------------|--|
| HDMI                        | HDMI 1.4 x 1   |
| DisplayPort                 | DisplayPort 1.2 x 1                                  |
| USB Hub                     | Yes  |
| USB Hub speed               | USB 3.2 (Gen 1) (4<br>USB downstream<br>ports) 5Gbit |
| USB downstream ports        | 4  |
| USB fast charge port        | Yes  |
| D-SUB (VGA)                 | 1x   |
| DVI                         | 1x DVI-D   |
| Speakers                    | Yes  |
| Speaker power               | 2 W x 2  |
| Built-in Microphone         | No   |
| Audio Output                | Headphone out (3.5mm)                                |

| PRODUCT DIMENSIONS (METRIC)              |                      |
|--|----------------------|
| Product dimensions incl. base (WxHxD) mm | 540.2 x 513 x 200.1  |
| Product dimensions excl. base (WxHxD) mm | 540.2 x 326.4 x 50.7 |
| Packaging dimensions (WxHxD) mm          | 610 x 525 x 160      |
| Gross weight incl. package (in kg)       | 6,89                 |
| Product with stand (kg)                  | 4,75                 |