# ЛОС



## 24B3CF2

Compact brilliance with USB-C connectivity and Height-Adjustable Stands for enhanced productivity

Introducing the newest addition to the B3 line– a brilliant 23,8-inch display featuring an IPS panel for breathtaking visuals and true-tolife colors. If you're looking for a compact sized monitor, the 24B3CF2 is the ideal choice. Also, it offers USB-C which means it is possible to catch three birds with one stone. By one single cable, video signal, power delivery and data transfer are available which will improve your productivity. This monitor boasts heightadjustable stands, seamlessly integrating ergonomic features into your workspace. With the ability to customize the height according to your preferences, you can achieve the perfect viewing angle, reducing strain on your neck and eyes during extended work or studying sessions. Whether you're working or studying, enjoy a more comfortable and enjoyable viewing experience with the compact screen size of the 24B3CF2.

GENERAL	
Model Name	24B3CF2
EAN	4038986141437
Channel	B2C
Product line	Basic-line
Design family	В3
Launch date (ETA)	1/1/2024

#### **/IOC**

SCREEN	
Screen size (inch)	23.8
Screen size (cm)	60.5
Flat / Curved	Flat
Display hardness	ЗН
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	IPS
Backlight type	WLED
Max Refresh rate	100 Hz
Response time GtG	4 ms
Response time MPRT	1 ms
Static contrast ratio	1300:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2745
Pixels per Inch	93

EXTERIOR	
Bezel type (front)	Ultra Narrow
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100x100
Tilt	-5 (+3/-0) ~ +23 (-3/+0)
Swivel	No
Pivot	Νο
Height adjust (mm)	110mm

### ЛОС

CONNECTIVITY AND MULTIMEDIA	
НДМІ	HDMI 1.4 x 1
Digital HDCP (HDMI version)	HDCP 1.4
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	✓ ·
USB Hub speed	USB 3.2 (Gen 1)
USB downstream ports	2
USB fast charge port	×
RJ45	Νο
D-SUB (VGA)	0x
DVI	0x

MULTIMEDIA	
Speakers	$\checkmark$
Speaker power	2 W x 2
Built-in Microphone	-
Audio Output	1x Audio out
MonitorWebcam	No

FEATURES	
Sync technology (VRR)	Adaptive Sync
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
KVM	No
Kensington Lock	
Colour space (sRGB) CIE 1976 %	102.5
Colour space (DCI-P3) CIE 1931 %	75.7
Colour space (DCI-P3) CIE 1976 %	81.6
Colour space (Adobe RGB) CIE 1931 %	76.1
Colour space (Adobe RGB) CIE 1976 %	87.8

SUSTAINABILITY	
TCO Certified	Νο
Energy star	Energy star 8

#### **/IOC**

POWER / ENVIRONMENTAL	
Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3
Energy class	E

PRODUCT DIMENSIONS	
Product dimensions incl. base (WxHxD) mm	542.4 x (359.9-469.9) x 229.8
Product dimensions excl. base (WxHxD) mm	542.4 x 316.2 x 44.6
Packaging dimensions (WxHxD) mm	613 x 519 x 162
Packaging dimensions (WxHxD) mm (CN)	613 x 519 x 162
Gross weight incl. package (in kg)	7.04
Net weight excl. package (in kg)	4.56
Gross weight incl. package (in kg) (CN)	7.04
Product without stand (kg)	3.04

WHAT'S IN THE BOX	
HDMI cable	1.5
USB-C to C cable	1.8
RS232	-
Power Cable	<i>v</i>
Color and brightness uniformity report in box	-

OTHER INFORMATION	
MTBF (including panel)	30.000 hours