



## E2275SWQE

### Vibrant viewing, energy-efficient performance

This model targets business and home office users alike. Hidden behind its classically designed case is the latest LED technology. It boasts a high typical contrast, an ultra-fast response time and wide viewing angles for excellent imaging performance. With the i-Care function, the monitor adapts the panel's brightness to the ambient light. This means a more comfortable viewing experience, whilst lowering the energy consumption at the same time. The environmentally friendly display comes in an elegant, textured black finish.

### GENERAL

Model Name	E2275SWQE
EAN	4038986126144
Channel	B2B
Product line	Essential-line
Design family	75 ID
Launch date (ETA)	12/30/2014

### SCREEN

Screen size (inch)	21.5
Flat / Curved	Flat
Display hardness	3H
Panel resolution	1920x1080
Resolution name	FHD
Panel type	TN
Backlight type	WLED
Max Refresh rate	60 Hz
Response time GtG	2 ms
Static contrast ratio	1000:1
Dynamic contrast ratio	200M:1
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	248

**ERGONOMICS**

Vesa wallmount	100x100
Pivot	No

**CONNECTIVITY AND MULTIMEDIA**

HDMI	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.1 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x

**MULTIMEDIA**

Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

**FEATURES**

Flicker-Free	Flicker Free
Kensington Lock	-

**SUSTAINABILITY**

TCO Certified	7
---------------	---

**POWER / ENVIRONMENTAL**

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.3
Power consumption off in watts	0.3
Energy class	A

**PRODUCT DIMENSIONS**

Product dimensions incl. base (WxHxD) mm	193.5(H) x 504(W) x 395.4(D)
Packaging dimensions (WxHxD) mm	390(H) x 560(W) x 120(D)
Gross weight incl. package (in kg)	4.5
Net weight excl. package (in kg)	3.15

**WHAT'S IN THE BOX**

Displayport cable	1.8
Power cable C13	1.8
D-SUB (VGA) cable	1.8

**OTHER INFORMATION**

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

**REGULATORY COMPLIANCE**

ISO 9241-307	-
--------------	---