



U2777PQU

Expand your productivity with 4K UHD

This 27" 4K IPS display offers highly detailed images and accurate colours (100 % sRGB) from every angle. Its ergonomic and input options (incl. DisplayPort) are first class as well.

GENERAL

Model Name	U2777PQU
EAN	4038986185776
Channel	B2B
Product line	Pro-line
Design family	77 ID
Launch date (ETA)	9/2/2016

SCREEN

Screen size (inch)	27
Screen size (cm)	68.58
Flat / Curved	Flat
Display hardness	3H
Panel resolution	3840x2160
Resolution name	UHD
Aspect ratio	16:9
Panel type	IPS
Backlight type	WLED
Max Refresh rate	60 Hz
Response time GtG	4 ms
Static contrast ratio	1000:1
Dynamic contrast ratio	80M:1
Viewing angle (CR10)	178/178
Display colours	1.07 Billion
Brightness in nits	350 cd/m2
Pixel Pitch (mm)	0.1554

EXTERIOR

Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Glossy
Cabinet colour (backside)	Silver, Black
Cabinet finishing (backside)	Texture

ERGONOMICS

Vesa wallmount	100x100
Tilt	-5/24
Swivel	-165/165
Pivot	Yes
Height adjust (mm)	130mm

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 2.0 x 1
DisplayPort	DisplayPort 1.2 x 1
USB Hub	✓
USB Hub speed	USB 2.0 + 3.0 (4 USB downstream ports)
USB downstream ports	4
D-SUB (VGA)	1x
DVI	1x DVI-D

MULTIMEDIA

Speakers	✓
Speaker power	3 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES

Flicker-Free	Flicker Free
Kensington Lock	-

SUSTAINABILITY

TCO Certified	7
Energy star	Energy star 8

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.76
Power consumption off in watts	0.21
Energy class	C

PRODUCT DIMENSIONS

Product dimensions incl. base (WxHxD) mm	531.15(H) x 614.9(W) x 194.27(D)
Packaging dimensions (WxHxD) mm	480(H) x 715(W) x 224(D)
Gross weight incl. package (in kg)	9.3
Net weight excl. package (in kg)	7.3

WHAT'S IN THE BOX

HDMI cable	1.8
DVI cable	1.8
Displayport cable	1.8
Audio cable	1.8
Power cable C7	1.8

OTHER INFORMATION

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE

ISO 9241-307	✓
--------------	---