



G2590FX

24.5", feature packed, sleek gaming at 144 Hz

It is fast! 144 Hz refresh rate coupled with 1 ms response time and FreeSync Premium support. 24.5" display in Full HD on a sleek, 3-sides frameless design.

GENERAL

Model Name	G2590FX
EAN	4038986166423
Channel	Gaming
Product line	AOC Gaming
Design family	G90
Launch date (ETA)	11/28/2017

SCREEN

Screen size (inch)	24.5
Screen size (cm)	62.23
Flat / Curved	Flat
Display hardness	3H
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	TN
Backlight type	WLED
Max Refresh rate	144 Hz
Response time GtG	1 ms
Static contrast ratio	1000:1
Dynamic contrast ratio	50M:1
Viewing angle (CR10)	170/160
Display colours	16.7 Million
Brightness in nits	400 cd/m2
Pixel Pitch (mm)	0.2832

EXTERIOR

Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black, Red
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS

Vesa wallmount	100x100
Tilt	-3,5/19,5
Pivot	No

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 1.4 x 2
DisplayPort	DisplayPort 1.2 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x

MULTIMEDIA

Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES

Sync technology (VRR)	Freesync Premium
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Colour space (Adobe RGB) CIE 1931 %	81

GAMING FEATURES

Gaming style	Shooters, Action, FPS (eSports)
Gaming convenience	G-menu

SUSTAINABILITY

TCO Certified	7
---------------	---

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.5
Energy class	F

PRODUCT DIMENSIONS

Product dimensions incl. base (WxHxD) mm	558.6(H) x 199.7(W) x 423.7(D)
Packaging dimensions (WxHxD) mm	417(H) x 627(W) x 173(D)
Gross weight incl. package (in kg)	6.1
Net weight excl. package (in kg)	4.27

WHAT'S IN THE BOX

HDMI cable	1.8
Displayport cable	1.8

OTHER INFORMATION

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE

ISO 9241-307	✓
--------------	---