

CU34P3CV

34 inch (86.36 cm) LCD MONITOR



The AOC CU34P3CV is a 34" WOH (3440 × 1440) curved VA screen with an attractive three-sided ultrathin bezel design that offers truly immersive viewing. This model's Wide QHD 21:9 aspect ratio expands your field of vision while providing a wrap-around view for an enhanced cinematic experience. The panel features 300-nit brightness and generous 178/178° wide viewing angles, along with two built-in 5W + 5W speakers to enhance your daily productivity in today's Wxible office. Monitor CU34P3CV is ready to boost your productivity with USB-C supporting Power Delivery up to 65W, data transfer and DP-alt mode. Connectivity of this monitor is enhanced with USB Hub and RJ-45. Keeping sustainability in mind, an array of environmental certifications including EPA, TCO, and EPEAT complete this monitor.

GENERAL

Model Name	CU34P3CV
EAN	4038986110730
Channel	B2B
Product line	Pro-line
Design family	P3

SCREEN	
Screen size (inch)	34
Screen size (cm)	86.36
Flat / Curved	Curved
Curvature Radius	1500R
Display hardness	3H
Panel treatment	Antiglare (AG)
Panel resolution	3440x1440
Aspect ratio	21:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	100 Hz
Response time GtG	4 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0.23175

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100x100
Tilt	-5~20°
Swivel	175°±5
Pivot	-90°~90°
Height adjust (mm)	150mm

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 2.0 x 1
DisplayPort	DisplayPort 1.4 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	✓
USB Hub speed	USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit
USB downstream ports	4
RJ45	1x 10M/100M/1G

MULTIMEDIA

Speakers	✓
Speaker power	5 W x 2
Audio Output	1x Audio out

FEATURES

Multiview (PbP, PiP)	PiP+PbP
Flicker-Free	Flicker Free
KVM	1x USB3.2 Gen 2 type C + 1x type B
Kensington Lock	✓

SUSTAINABILITY

TCO Certified	9
Energy star	Energy star 8

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3

PRODUCT DIMENSIONS

Product dimensions incl. base (WxHxD) mm	808.34 x (482.44-611.03) x275.13mm
Product dimensions excl. base (WxHxD) mm	808.34 x 367.45 x 104.7mm
Packaging dimensions (WxHxD) mm	1070(W) x 556(H) x 190(D) mm
Gross weight incl. package (in kg)	12.95
Net weight excl. package (in kg)	10

WHAT'S IN THE BOX

Power cable C13	1.8
-----------------	-----

OTHER INFORMATION

MTBF	30.000 hours
MTBF (excluding panel)	70.000 hours
MTBF (including panel)	30.000 hours