



Comfortable gaming headset with stereo sound, 3.5mm audio connection and detachable microphone

Do you prefer gaming on PC, consoles or your mobile phone? No matter your choice, the AOC GH200 can easily be plugged into any device thanks to the versatile 3.5mm audio connection. Stereo sound ensures the sound is perfectly mixed for an immersive feeling and the built-in detachable microphone allows you to communicate with teammates.

| GENERAL      |               |
|--------------|---------------|
| Modelname    | GH200         |
| EAN          | 4038986638968 |
| Channel      | Gaming        |
| Product line | AOC gaming    |

| CONNECTIVITY |                    |
|--------------|--------------------|
| Connectivity | Wired              |
| Connector    | Y-splitter, 3.5 mm |
| CableType    | Braided            |
| Cable length | 1.8 m              |

| WARRANTY        |         |
|-----------------|---------|
| Warranty period | 2 years |

| PRODUCT DIMENSIONS            |                 |
|-------------------------------|-----------------|
| Product dimensions (WxHxD) mm | 195x 100x 160   |
| Product weight kg             | 326.5           |
| Packaging dimensions (LxWxH)  | 405 x 560 x 475 |
| Packaging weight kg           | 639             |

| WHAT'S IN THE BOX  |                             |
|--------------------|-----------------------------|
| What's in the box? | Y-splitter, Gaming Headsets |

| COMPATIBILITY |                     |
|---------------|---------------------|
| Platform      | PC, Console, Mobile |

| ACOUSTICS       |   |
|-----------------|---|
| Audio channels  | Stereo  |
| Driver mode     | Moving Coil                                   |
| Driver diameter | 50 mm   |
| Driver material | PU+PEEK composite diaphragm, Neodymium Magnet |
| Impedance       | 32 Ω±15%                                      |
| Sensitivity     | 100 ± 3dB (at 1KH 1mW)                        |
| Balancecanals   | ≤3dB (at 1KH 1mW)                             |
| Rated power     | 15mW  |
| Max power       | 50 mW   |
| Frequency range | 20Hz - 20KHz                                  |

| MICROPHONE        |                      |
|-------------------|----------------------|
| Directionality    | Omnidirectional      |
| Operating voltage | 1.1V - 4.5V          |
| Sensitivity       | -38±3dB (0dB =1V/PA) |
| Impedance         | 2.2K(Max)            |
| Frequency range   | 100Hz - 10KHz        |