



24B2XHM2

Thin and sleek 23.8" VA monitor with lively colours, wide angle visibility and eye-friendly technology

The 24B2XHM2 from the B2 Series employs a 23.8" Full HD VA panel offering wide viewing angles, accurate and lively colours plus flexible connectivity. It features a slim profile and a 3-sides borderless panel for seamless multi monitor setups. Say goodbye to eyestrain thanks to AOC's LowBlue and FlickerFree technologies.

GENERAL	
Model Name	24B2XHM2
EAN	4038986149594
Channel	B2C
Product line	Basic-line
Design family	B2
Launch date (ETA)	1/15/2021

1/4



SCREEN	
Screen size (inch)	23.8
Screen size (cm)	60.452
Flat / Curved	Flat
Display hardness	ЗН
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	75 Hz
Response time GtG	4 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2745
Pixels per Inch	93

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100×100
Tilt	-5/21.5
Pivot	No



CONNECTIVITY AND MULTIMEDIA	
HDMI	HDMI 1.4 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x

MULTIMEDIA	
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES	
Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	/

POWER / ENVIRONMENTAL	
Power supply	External
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.3
Power consumption off in watts	0.3
Energy class	E

PRODUCT DIMENSIONS	
Product dimensions incl. base (WxHxD) mm	418.35(H) x 539.47(W) x 170.94(D)
Product dimensions excl. base (WxHxD) mm	320.94(H) x 539.47(W) x 37.6(D)
Packaging dimensions (WxHxD) mm	492(H) x 614(W) x 131(D)
Gross weight incl. package (in kg)	4.5
Net weight excl. package (in kg)	2.7

WHAT'S IN THE BOX	
HDMI cable	1.8
Power cable C13	1.8

3 / 4



OTHER INFORMATION	
MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE	
ISO 9241-307	/