



M2470SWDA2

23.6-inch WLED display with Full HD resolution, quick response times, high contrast ratios, built-in speakers and MVA panel technology for extra-wide viewing angles

The M2470SWDA2 display is the ideal solution for high-performance home computing with Full HD resolution and high contrast ratios for clear, detailed imagery. Advanced MVA panel technology delivers amazing 178-degree viewing angles and 4ms response time is perfect for graphics applications as well as fast-paced movies.

GENERAL

Model Name	M2470SWDA2
EAN	4038986145206
Channel	B2C
Product line	Basic-line
Design family	70 ID
Launch date (ETA)	12/29/2014

SCREEN

Screen size (inch)	23.6
Screen size (cm)	59.944
Flat / Curved	Flat
Display hardness	3H
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	MVA
Backlight type	WLED
Max Refresh rate	60 Hz
Response time GtG	5 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	50M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2715

EXTERIOR

Bezel type (front)	Normal
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS

Vesa wallmount	100x100
Tilt	-5/25
Pivot	No

CONNECTIVITY AND MULTIMEDIA

USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x
DVI	1x DVI-D

MULTIMEDIA

Speakers	✓
Speaker power	2 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES

Flicker-Free	No
Kensington Lock	-

SUSTAINABILITY

TCO Certified	6
---------------	---

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.37
Power consumption off in watts	0.19
Energy class	F

PRODUCT DIMENSIONS

Product dimensions incl. base (WxHxD) mm	400.4(H) x 551.4(W) x 221(D)
Packaging dimensions (WxHxD) mm	127(H) x 620(W) x 435(D)
Gross weight incl. package (in kg)	5.14
Net weight excl. package (in kg)	3.51

WHAT'S IN THE BOX

D-SUB (VGA) cable	1.2
DVI cable	1.5
Audio cable	1.5
Power cable C7	1.2

OTHER INFORMATION

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE

ISO 9241-307	-
--------------	---