



U34V5C/BK

34" VA WQHD display for the most complex multitasking, with USB-C and PD65W

The AOC U34V5C is equipped with a 34" VA panel with WQHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and adjust the height as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.

| GENERAL | |
|-------------------|---------------|
| Model Name | U34V5C/BK |
| EAN | 4038986110617 |
| Channel | B2C |
| Product line | Value-line |
| Design family | V5 |
| Launch date (ETA) | 10/13/2022 |

| SCREEN | |
|------------------------|----------------|
| Screen size (inch) | 34 |
| Screen size (cm) | 86.4 |
| Flat / Curved | Flat |
| Display hardness | 6H |
| Panel treatment | Antiglare (AG) |
| Panel resolution | 3440x1440 |
| Resolution name | WQHD |
| Aspect ratio | 21:9 |
| Panel type | VA |
| Backlight type | WLED |
| Max Refresh rate | 100 Hz |
| Response time GtG | 4 ms |
| Static contrast ratio | 4000:1 |
| Dynamic contrast ratio | 20M:1 |
| Viewing angle (CR10) | 178/178 |
| Display colours | 16.7 Million |
| Brightness in nits | 300 cd/m2 |
| Pixel Pitch (mm) | 0.23175 |
| Pixels per Inch | 109 |

| EXTERIOR | |
|------------------------------|-------------------|
| Bezel type (front) | 3-sided frameless |
| Bezel Colour (front) | Black |
| Bezel finishing (front) | Matt |
| Cabinet colour (backside) | Black |
| Cabinet finishing (backside) | Matt |

| ERGONOMICS | |
|--------------------|---------------------------|
| Vesa wallmount | 100x100 |
| Tilt | -3.5° ±1.5° ~ 21.5° ±1.5° |
| Swivel | -8° ±2° |
| Pivot | No |
| Height adjust (mm) | 130mm |

CONNECTIVITY AND MULTIMEDIA

| | |
|-----------------------------|------------------------------------------------------------------|
| HDMI | HDMI 2.0 x 1 |
| Digital HDCP (HDMI version) | HDCP 2.0 |
| DisplayPort | DisplayPort 1.2 x 1 |
| USB-C connectivity | USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W) |
| USB Hub | ✓ |
| USB Hub speed | USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit |
| USB downstream ports | 4 |
| USB fast charge port | ✓ |
| RJ45 | No |
| D-SUB (VGA) | 0x |
| DVI | 0x |

MULTIMEDIA

| | |
|---------------------|-----------------------|
| Speakers | ✓ |
| Speaker power | 5 W x 2 |
| Built-in Microphone | - |
| Audio Output | Headphone out (3.5mm) |
| Monitor Webcam | No |

FEATURES

| | |
|-------------------------------------|----------------|
| Sync technology (VRR) | Adaptive Sync |
| Blue Light Technology | Low Blue Light |
| Multiview (PbP, PiP) | PbP, PiP |
| Flicker-Free | Flicker Free |
| KVM | No |
| Kensington Lock | ✓ |
| Colour space (sRGB) CIE 1976 % | 115 |
| Colour space (DCI-P3) CIE 1931 % | 89 |
| Colour space (DCI-P3) CIE 1976 % | 91 |
| Colour space (Adobe RGB) CIE 1931 % | 90 |
| Colour space (Adobe RGB) CIE 1976 % | 98 |

SUSTAINABILITY

| | |
|---------------|----|
| TCO Certified | No |
|---------------|----|

POWER / ENVIRONMENTAL

| | |
|------------------------------------|--------------------|
| Power supply | Internal |
| Power source | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0.5 |
| Power consumption off in watts | 0.3 |
| Energy class | G |

PRODUCT DIMENSIONS

| | |
|------------------------------------------|--------------------------------|
| Product dimensions incl. base (WxHxD) mm | 817.45 x (404.55~534.55) x 250 |
| Product dimensions excl. base (WxHxD) mm | 817.45 x 370.69 x 55.34 |
| Packaging dimensions (WxHxD) mm | 1070 x 481 x 162 |
| Gross weight incl. package (in kg) | 11.65 |
| Net weight excl. package (in kg) | 9.14 |
| Product without stand (kg) | 6.56 |

WHAT'S IN THE BOX

| | |
|------------------|-----|
| HDMI cable | 1.5 |
| USB-C to C cable | 1.8 |

OTHER INFORMATION

| | |
|------------------------|-----------------------------------|
| MTBF | 50.000 hours (excluded backlight) |
| MTBF (including panel) | 50.000 hours |