



## Q3277PQU

### Ergonomic 32" QHD display with 100 % sRGB

This large 32" QHD monitor produces highly detailed images in accurate colours (100 % sRGB). It also boasts ergonomic options as well as DisplayPort, HDMI and USB connectors.

#### GENERAL

Model Name	Q3277PQU
EAN	4038986115438
Channel	B2B
Product line	Pro-line
Design family	77 ID
Launch date (ETA)	7/31/2015

#### SCREEN

Screen size (inch)	32
Screen size (cm)	81.28
Flat / Curved	Flat
Display hardness	3H
Panel resolution	2560x1440
Resolution name	QHD
Aspect ratio	16:9
Panel type	MVA
Backlight type	WLED
Max Refresh rate	60 Hz
Response time GtG	4 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	80M:1
Viewing angle (CR10)	178/178
Display colours	1.07 Billion
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0.276

**EXTERIOR**

Bezel type (front)	Narrow
Bezel Colour (front)	Black
Bezel finishing (front)	Glossy
Cabinet colour (backside)	Silver, Black
Cabinet finishing (backside)	Glossy

**ERGONOMICS**

Vesa wallmount	100x100
Tilt	-5/24
Swivel	-165/165
Pivot	Yes
Height adjust (mm)	180mm

**CONNECTIVITY AND MULTIMEDIA**

HDMI	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.2 x 1
USB Hub	✓
USB Hub speed	USB 2.0 + 3.0 (4 USB downstream ports)
USB downstream ports	4
D-SUB (VGA)	1x
DVI	1x DVI-D

**MULTIMEDIA**

Speakers	✓
Speaker power	3 W x 2
Audio Output	Headphone out (3.5mm)

**FEATURES**

Flicker-Free	Flicker Free
--------------	--------------

**SUSTAINABILITY**

TCO Certified	6
---------------	---

**POWER / ENVIRONMENTAL**

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.5
Energy class	B

**PRODUCT DIMENSIONS**

Product dimensions incl. base (WxHxD) mm	659(H) x 741.88(W) x 171.2(D)
Packaging dimensions (WxHxD) mm	248(H) x 577(W) x 858(D)
Gross weight incl. package (in kg)	15.31
Net weight excl. package (in kg)	11.55

**WHAT'S IN THE BOX**

HDMI cable	1.8
D-SUB (VGA) cable	1.8
DVI cable	1.8
Displayport cable	1.8
Audio cable	1.8
Power cable C7	1.8

**OTHER INFORMATION**

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

**REGULATORY COMPLIANCE**

ISO 9241-307	✓
--------------	---