



1960SRDA

19" 5:4 IPS display with speakers

This $5:4\ 19"$ IPS display comes with wide viewing angles, DVI connectivity and integrated speakers, which make it a good choice for demanding office users.

GENERAL	
Model Name	I960SRDA
Channel	B2B
Product line	Essential-line
Design family	60 ID
Launch date (ETA)	12/29/2014

Screen size (inch) 19 Screen size (cm) 48.26 Flat / Curved Flat Display hardness 3H Panel resolution 1280x1024 Resolution name SXGA Aspect ratio 5:4 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2 Pixel Pitch (mm) 0.294	SCREEN	
Flat / Curved Display hardness 3H Panel resolution 1280x1024 Resolution name SXGA Aspect ratio 5:4 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) Display colours Brightness in nits Flat 1280x1024 SXGA Aspect ratio 5:4 Panel type IPS SXGA Panel type IPS SXGA Aspect ratio 5:4 Panel type IPS SXGA Aspect ratio 5:4 Panel type IPS SYGA Panel type IPS SYGA Panel type IPS IPS IPS IPS IPS IPS IPS IP	Screen size (inch)	19
Display hardness 3H Panel resolution 1280x1024 Resolution name SXGA Aspect ratio 5:4 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Screen size (cm)	48.26
Panel resolution 1280x1024 Resolution name SXGA Aspect ratio 5:4 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Flat / Curved	Flat
Resolution name SXGA Aspect ratio 5:4 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio Dynamic contrast ratio 20M:1 Viewing angle (CR10) Display colours 16.7 Million Brightness in nits	Display hardness	ЗН
Aspect ratio 5:4 Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Panel resolution	1280x1024
Panel type IPS Backlight type WLED Max Refresh rate 75 Hz Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Resolution name	SXGA
Backlight typeWLEDMax Refresh rate75 HzResponse time GtG5 msStatic contrast ratio1000:1Dynamic contrast ratio20M:1Viewing angle (CR10)178/178Display colours16.7 MillionBrightness in nits250 cd/m2	Aspect ratio	5:4
Max Refresh rate75 HzResponse time GtG5 msStatic contrast ratio1000:1Dynamic contrast ratio20M:1Viewing angle (CR10)178/178Display colours16.7 MillionBrightness in nits250 cd/m2	Panel type	IPS
Response time GtG 5 ms Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Backlight type	WLED
Static contrast ratio 1000:1 Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Max Refresh rate	75 Hz
Dynamic contrast ratio 20M:1 Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Response time GtG	5 ms
Viewing angle (CR10) 178/178 Display colours 16.7 Million Brightness in nits 250 cd/m2	Static contrast ratio	1000:1
Display colours 16.7 Million Brightness in nits 250 cd/m2	Dynamic contrast ratio	20M:1
Brightness in nits 250 cd/m2	Viewing angle (CR10)	178/178
	Display colours	16.7 Million
Pixel Pitch (mm) 0.294	Brightness in nits	250 cd/m2
	Pixel Pitch (mm)	0.294

1/3



EXTERIOR	
Bezel type (front)	Normal
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100×100
Tilt	-5/20
Pivot	No

CONNECTIVITY AND MULTIMEDIA	
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x
DVI	1x DVI-D

MULTIMEDIA	
Speakers	✓
Speaker power	2 W x 2
Built-in Microphone	-

FEATURES	
Flicker-Free	No
Kensington Lock	-

SUSTAINABILITY	
TCO Certified	6
Energy star	Energy star 8



POWER / ENVIRONMENTAL	
Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.27
Power consumption off in watts	0.21
Energy class	E

PRODUCT DIMENSIONS (METRIC)	
Product dimensions incl. base (WxHxD) mm	405.1(H) x 409.2(W) x 210(D)
Packaging dimensions (WxHxD) mm	114(H) x 463(W) x 459(D)
Gross weight incl. package (in kg)	4.2
Product with stand (kg)	2.85

WHAT'S IN THE BOX	
D-SUB (VGA) cable	1.8

OTHER INFORMATION	
MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE	
ISO 9241-307	-