



I2475PXJ/GR

Stunning performance that puts comfort first.

At home or the office, this monitor offers excellent performance with 16.7 million colors and 4ms response time. The height-adjustable stand tilts, swivels and even pivots 90 degrees for optimal viewing and comfort.

GENERAL

| | |
|-------------------|-------------|
| Model Name | I2475PXJ/GR |
| Channel | B2B |
| Product line | Pro-line |
| Design family | 75 ID |
| Launch date (ETA) | 12/29/2014 |

SCREEN

| | |
|------------------------|--------------|
| Screen size (inch) | 23.8 |
| Screen size (cm) | 60.452 |
| Flat / Curved | Flat |
| Display hardness | 3H |
| Panel resolution | 1920x1080 |
| Resolution name | FHD |
| Aspect ratio | 16:9 |
| Panel type | IPS |
| Backlight type | WLED |
| Max Refresh rate | 60 Hz |
| Response time GtG | 4 ms |
| Static contrast ratio | 1000:1 |
| Dynamic contrast ratio | 50M:1 |
| Viewing angle (CR10) | 178/178 |
| Display colours | 16.7 Million |
| Brightness in nits | 250 cd/m2 |
| Pixel Pitch (mm) | 0.2745 |

EXTERIOR

| | |
|------------------------------|---------|
| Bezel type (front) | Normal |
| Bezel Colour (front) | Grey |
| Bezel finishing (front) | Texture |
| Cabinet colour (backside) | Grey |
| Cabinet finishing (backside) | Texture |

ERGONOMICS

| | |
|--------------------|----------|
| Vesa wallmount | 100x100 |
| Tilt | -5/25 |
| Swivel | -165/165 |
| Pivot | Yes |
| Height adjust (mm) | 130mm |

CONNECTIVITY AND MULTIMEDIA

| | |
|----------------------|--------------|
| HDMI | HDMI 1.4 x 1 |
| USB Hub | - |
| USB fast charge port | - |
| D-SUB (VGA) | 1x |
| DVI | 1x DVI-D |

MULTIMEDIA

| | |
|---------------------|-----------------------|
| Speakers | ✓ |
| Speaker power | 2 W x 2 |
| Built-in Microphone | - |
| Audio Output | Headphone out (3.5mm) |

FEATURES

| | |
|-----------------|--------------|
| Flicker-Free | Flicker Free |
| Kensington Lock | - |

SUSTAINABILITY

| | |
|---------------|---|
| TCO Certified | 7 |
|---------------|---|

POWER / ENVIRONMENTAL

| | |
|------------------------------------|--------------------|
| Power supply | Internal |
| Power source | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0.3 |
| Power consumption off in watts | 0.3 |

PRODUCT DIMENSIONS (METRIC)

| | |
|--|--------------------------------|
| Product dimensions incl. base (WxHxD) mm | 423.7(H) x 554.4(W) x 193.5(D) |
| Packaging dimensions (WxHxD) mm | 415(H) x 670(W) x 182(D) |
| Product with stand (kg) | 6 |

WHAT'S IN THE BOX

| | |
|-------------------|-----|
| D-SUB (VGA) cable | 1.8 |
|-------------------|-----|

OTHER INFORMATION

| | |
|------------------------|-----------------------------------|
| MTBF | 50.000 hours (excluded backlight) |
| MTBF (excluding panel) | 50.000 hours |

REGULATORY COMPLIANCE

| | |
|--------------|---|
| ISO 9241-307 | - |
|--------------|---|