



Q27P1/GR

27" ergonomic IPS display with high QHD resolution

High pixel density thanks to 27" size and QHD (2560x1440px) resolution, which equals the content of four 720p screens. The IPS panel of the Q27P1 offers accurate colours and wide viewing angles. The ergonomic stand offers "Easy Assembly" and full 150 mm height adjustment, in addition to tilt, swivel and pivot modes. Q27P1 offers current (HDMI & DP) and legacy (VGA & DVI) display inputs, built-in speakers, and a USB 3.0 hub for the utmost versatility.

GENERAL

Model Name	Q27P1/GR
Channel	B2B
Product line	Pro-line
Design family	P1
Launch date (ETA)	8/1/2018

SCREEN

Screen size (inch)	27
Flat / Curved	Flat
Display hardness	3H
Panel resolution	2560x1440
Resolution name	QHD
Aspect ratio	16:9
Panel type	IPS
Backlight type	WLED
Max Refresh rate	60 Hz
Response time GtG	5 ms
Static contrast ratio	1000:1
Dynamic contrast ratio	50M:1
Viewing angle (CR10)	178/178
Display colours	1.07 Billion
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2331

ERGONOMICS

Vesa wallmount	100x100
Pivot	Yes
Height adjust (mm)	150mm

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.2 x 1
USB Hub speed	USB 3.1 (Gen 1)
D-SUB (VGA)	1x
DVI	1x DVI-D

MULTIMEDIA

Speakers	✓
Speaker power	2 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES

Flicker-Free	Flicker Free
Kensington Lock	✓
Colour space (Adobe RGB) CIE 1931 %	75

SUSTAINABILITY

TCO Certified	7
---------------	---

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.36
Power consumption off in watts	0.25
Energy class	E

PRODUCT DIMENSIONS (METRIC)

Product dimensions incl. base (WxHxD) mm	548.5(H) x 627.9(W) x 202.96(D)
Packaging dimensions (WxHxD) mm	478(H) x 827(W) x 186(D)
Gross weight incl. package (in kg)	8.8
Product with stand (kg)	6.1

WHAT'S IN THE BOX

HDMI cable	1.5
Displayport cable	1.8
Audio cable	1.5
Power cable C13	1.8

OTHER INFORMATION

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE

ISO 9241-307	✓
--------------	---