

## CU34P2C



**Productivity, USB-C connectivity, and comfort in a curved 1500R 34" ultra wide QHD display**

Professional users looking for a true productivity ally need look no further than the CU34P2C. This model is equipped with a curved 1500R 34" VA/3FL screen with 21:9 ultra wide QHD resolution and 300 cd/m2 brightness. Its rich, innovative features include wide viewing angles of 178°/178°, HDMI and DP compatibility, a USB-C, and USB 3.2 hub, and auto source input.

GENERAL	
Model Name	CU34P2C
Channel	B2B
Product line	Pro-line
Design family	P2
Launch date (ETA)	7/1/2020

SCREEN	
Screen size (inch)	34
Screen size (cm)	86.36
Flat / Curved	Curved
Curvature Radius	1500R
Display hardness	3H
Panel treatment	Antiglare (AG)
Panel resolution	3440x1440
Resolution name	WQHD
Aspect ratio	21:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	100 Hz
Response time GtG	4 ms
Response time MPRT	1 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	50M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	300 cd/m2
Pixel Pitch (mm)	0.2745

EXTERIOR	
Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS	
Vesa wallmount	100x100
Tilt	-5/23
Swivel	-180/180
Pivot	No
Height adjust (mm)	150mm

**CONNECTIVITY AND MULTIMEDIA**

HDMI	HDMI 2.0 x 1
DisplayPort	DisplayPort 1.2 x 1
USB-C connectivity	USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W)
USB Hub	✓
USB Hub speed	USB 3.2 (Gen 1) (4 USB downstream ports) 5Gbit
USB downstream ports	4
USB fast charge port	✓

**MULTIMEDIA**

Speakers	✓
Speaker power	3 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

**FEATURES**

Sync technology (VRR)	Adaptive Sync
Blue Light Technology	Low Blue Light
Multiview (PbP, PiP)	PbP, PiP
Flicker-Free	Flicker Free
KVM	1x USB3.2 Gen 2 type C + 1x type B
Kensington Lock	✓

**SUSTAINABILITY**

TCO Certified	8
Energy star	Energy star 8
EPEAT	Silver

**POWER / ENVIRONMENTAL**

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.3
Energy class	G

**PRODUCT DIMENSIONS (METRIC)**

Product dimensions incl. base (WxHxD) mm	611.53(H) x 808.34(W) x 275.13(D)
Product dimensions excl. base (WxHxD) mm	367.45(H) x 808.34(W) x 100.14(D)
Packaging dimensions (WxHxD) mm	527(H) x 903(W) x 250(D)
Gross weight incl. package (in kg)	12.7
Product with stand (kg)	9.8

**WHAT'S IN THE BOX**

HDMI cable	1.8
Displayport cable	1.8
Power cable C13	1.8