



E2460PQ/BK

Beautiful imagery, impressive performance

This ergonomically adjustable and energy efficient business monitor boasts DisplayPort and HDMI connectors for high-speed digital input, as well as stereo speakers.

GENERAL

| | |
|-------------------|------------|
| Model Name | E2460PQ/BK |
| Channel | B2B |
| Product line | Pro-line |
| Design family | 60 ID |
| Launch date (ETA) | 12/30/2014 |

SCREEN

| | |
|------------------------|--------------|
| Screen size (inch) | 24 |
| Flat / Curved | Flat |
| Display hardness | 3H |
| Panel resolution | 1920x1080 |
| Resolution name | FHD |
| Aspect ratio | 16:9 |
| Panel type | TN |
| Backlight type | WLED |
| Max Refresh rate | 60 Hz |
| Response time GtG | 2 ms |
| Static contrast ratio | 1000:1 |
| Dynamic contrast ratio | 50M:1 |
| Viewing angle (CR10) | 170/160 |
| Display colours | 16.7 Million |
| Brightness in nits | 250 cd/m2 |
| Pixel Pitch (mm) | 276 |

ERGONOMICS

| | |
|--------------------|---------|
| Vesa wallmount | 100x100 |
| Pivot | Yes |
| Height adjust (mm) | 130mm |

CONNECTIVITY AND MULTIMEDIA

| | |
|-------------|---------------------|
| DisplayPort | DisplayPort 1.1 x 1 |
| USB Hub | - |
| D-SUB (VGA) | 1x |
| DVI | 1x DVI-D |

MULTIMEDIA

| | |
|--------------|-----------------------|
| Audio Output | Headphone out (3.5mm) |
|--------------|-----------------------|

SUSTAINABILITY

| | |
|---------------|---|
| TCO Certified | 6 |
|---------------|---|

POWER / ENVIRONMENTAL

| | |
|------------------------------------|--------------------|
| Power supply | Internal |
| Power source | 100 - 240V 50/60Hz |
| Power consumption standby in watts | 0.5 |
| Power consumption off in watts | 0.5 |

PRODUCT DIMENSIONS (METRIC)

| | |
|--|------------------------------|
| Product dimensions incl. base (WxHxD) mm | 400.4(H) x 551.4(W) x 221(D) |
| Packaging dimensions (WxHxD) mm | 187(H) x 693(W) x 423(D) |
| Gross weight incl. package (in kg) | 8.45 |
| Product with stand (kg) | 6.38 |

WHAT'S IN THE BOX

| | |
|-------------------|-----|
| Displayport cable | 1.8 |
| D-SUB (VGA) cable | 1.8 |

OTHER INFORMATION

| | |
|------------------------|-----------------------------------|
| MTBF | 50.000 hours (excluded backlight) |
| MTBF (excluding panel) | 50.000 hours |

REGULATORY COMPLIANCE

| | |
|--------------|---|
| ISO 9241-307 | ✓ |
|--------------|---|