



22E1Q

Contrast-rich, 21.5" MVA display with Full HD

The affordable 22E1Q MVA panel combines wide viewing angles with rich contrast. Low Blue Light and Flicker-Free technologies, built-in speakers plus its sleek stand with tilt adjustment increase comfort. Environmentally friendly, certified.

GENERAL

Model Name	22E1Q
Channel	B2B
Product line	Essential-line
Design family	E1
Launch date (ETA)	6/28/2018

SCREEN

Screen size (inch)	21.5
Screen size (cm)	54.61
Flat / Curved	Flat
Display hardness	3H
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	MVA
Backlight type	WLED
Max Refresh rate	60 Hz
Response time GtG	5 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2479

EXTERIOR

Bezel type (front)	Normal
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

ERGONOMICS

Vesa wallmount	100x100
Tilt	-5/21,5
Pivot	No

CONNECTIVITY AND MULTIMEDIA

HDMI	HDMI 1.4 x 1
DisplayPort	DisplayPort 1.2 x 1
USB fast charge port	-
D-SUB (VGA)	1x

MULTIMEDIA

Speakers	✓
Speaker power	2 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

FEATURES

Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Colour space (Adobe RGB) CIE 1931 %	72

SUSTAINABILITY

TCO Certified	7
Energy star	Energy star 8
EPEAT	Silver

POWER / ENVIRONMENTAL

Power supply	Internal
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.5
Power consumption off in watts	0.5
Energy class	E

PRODUCT DIMENSIONS (METRIC)

Product dimensions incl. base (WxHxD) mm	393.7(H) x 504.4(W) x 199.4(D)
Packaging dimensions (WxHxD) mm	401(H) x 564(W) x 137(D)
Gross weight incl. package (in kg)	4.3
Product with stand (kg)	2.72

WHAT'S IN THE BOX

HDMI cable	1.8
Displayport cable	1.8
Audio cable	1.5
Power cable C13	1.8

OTHER INFORMATION

MTBF	50.000 hours (excluded backlight)
MTBF (excluding panel)	50.000 hours

REGULATORY COMPLIANCE

ISO 9241-307	✓
--------------	---