



## 22B2AM

**Modern and sleek 21.5" 3-sides borderless monitor with Full HD and eye-caring LowBlue and FlickerFree technology**

Modernized design and crisp Full HD images. The 22B2AM combines a sleek 3-sides frameless panel and VGA and HDMI connectivity. Enjoy working or streaming with wide viewing angles and eye-soothing LowBlue and FlickerFree technologies.

### GENERAL

Model Name	22B2AM
Channel	B2C
Product line	Basic-line
Design family	B2
Launch date (ETA)	1/15/2020

### SCREEN

Screen size (inch)	21.5
Screen size (cm)	54.43
Flat / Curved	Flat
Display hardness	3H
Panel treatment	Antiglare (AG)
Panel resolution	1920x1080
Resolution name	FHD
Aspect ratio	16:9
Panel type	VA
Backlight type	WLED
Max Refresh rate	75 Hz
Response time GtG	4 ms
Static contrast ratio	3000:1
Dynamic contrast ratio	20M:1
Viewing angle (CR10)	178/178
Display colours	16.7 Million
Brightness in nits	250 cd/m2
Pixel Pitch (mm)	0.2482
Pixels per Inch	103

**EXTERIOR**

Bezel type (front)	3-sided frameless
Bezel Colour (front)	Black
Bezel finishing (front)	Texture
Cabinet colour (backside)	Black
Cabinet finishing (backside)	Texture

**ERGONOMICS**

Vesa wallmount	100x100
Tilt	-5/21,5
Pivot	No

**CONNECTIVITY AND MULTIMEDIA**

HDMI	HDMI 1.4 x 1
USB Hub	-
USB fast charge port	-
D-SUB (VGA)	1x

**MULTIMEDIA**

Speakers	✓
Speaker power	2 W x 2
Built-in Microphone	-
Audio Output	Headphone out (3.5mm)

**FEATURES**

Blue Light Technology	Low Blue Light
Flicker-Free	Flicker Free
Kensington Lock	✓

**POWER / ENVIRONMENTAL**

Power supply	External
Power source	100 - 240V 50/60Hz
Power consumption standby in watts	0.3
Power consumption off in watts	0.3
Energy class	E

**PRODUCT DIMENSIONS (METRIC)**

Product dimensions incl. base (WxHxD) mm	388.11(H) x 492.78(W) x 162.94(D)
Product dimensions excl. base (WxHxD) mm	292.68(H) x 492.78(W) x 36.2(D)
Packaging dimensions (WxHxD) mm	370(H) x 550(W) x 120(D)
Gross weight incl. package (in kg)	3.5
Product with stand (kg)	2.1

**WHAT'S IN THE BOX**

HDMI cable	1.5
Power cable C13	1.5

**REGULATORY COMPLIANCE**

ISO 9241-307	✓
--------------	---